

NOTES

MATERIAL

Insulator: Thermal Plastic UL94V-0

Contacts: Copper Alloy

Mount ear: Copper Alloy

CONTACT PLATING

Underplated: 50u"~100u" Nickel

Contact area: 1u"~30u" Selective gold




Solder tails area: 100u"~200u" Tin/Lead Free

Part no.

752 D E 50 N A 0 1 0 0 1
1 2 3 4 5 6 7 8 9 10 11

POWER	5.00mm	1,13,38,50
GENERAL	4.25mm	all other pins
DETECT	3.50mm	25,26
Pin type	Interface	Pin No.
	Dim. L	

- | | |
|---|--|
| 1. SERIES NO
752=C.F.A. | 6. CONTACT PLATING
Selective gold plating |
| 2. TYPE
D=SMT TYPE | A= 5u" Gold (selective) |
| 3. ENVIRONMENT PROTECTION
MATERIAL:
F=RoHS環保料件,電鍍霧錫 | C=15u" Gold (selective) |
| 4. CONTACT NUMBER
50 = 50PIN | 7. STAND OFF DISTANCE
0=1.64 mm |
| 5. CONTACT TYPE
N=MALE(TYPE 1)一體端子 | 8. CARD KEY ORIENTATION STYLE
1=REVERSE |
| | 9. LOCK OPTION
0=WITHOUT |
| | 10. FILL IT WITH "0" |
| | 11. INSULATOR COLOR
1=WHITE |



RECOMMENDED P.C.B LAYOUT
TOLERANCES: ±0.05mm

UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG.	±5°
0.	±0.5
.0	±0.3
.00	±0.2

SCALE: AS SHOWN UNIT: mm

DRAWN	JUDY	09/04/07
CHECKED	TONY	09/04/07
APPROVED	ARVEN	09/04/07

深圳市金聯電子有限公司
Gold Link Electronic.

TEL:+86-755-83748558 FAX:+86-755-83748559

DRAWN NAME:
CF TYPE-1 板下型,STF=1.64mm 白色
ROHS環保料件,電鍍霧錫,一體端子

PRODUCT NO. 752DF50NA01001

FILE NAME: 752DF50NA01001

REV.	DESCRIPTION	DATE
B	ECN-070904001(TONY) (6,B)(7,B)	09/04/07
A	ECN-070728001(TONY)	07/28/07