



Introduction

This data sheet provides package information for Altera® devices. It includes these sections:

- [Device & Package Cross Reference](#) (below)
- [Thermal Resistance](#) (starting on page 16)
- [Package Outlines](#) (starting on page 35)

In this data sheet, packages are listed in order of ascending pin count.

Device & Package Cross Reference

Table 1 through 14 show the devices available in Ball-Grid Array (BGA), FineLine BGA® (FBGA), Ultra FineLine BGA (UBGA), Micro FineLine BGA (MBGA), Pin-Grid Array (PGA), Plastic J-Lead Chip Carrier (PLCC), Thin Quad Flat Pack (TQFP), Plastic Quad Flat Pack (PQFP), Ceramic Dual In-Line Package (CerDIP), and Hybrid FineLine BGA (HBGA):

- Stratix® series FPGAs
- Cyclone™ series FPGAs
- MAX® series CPLDs
- HardCopy® series Structured ASICs
- APEX™ series FPGAs
- ACEX® 1K FPGAs
- Mercury™ FPGAs
- FLEX® series FPGAs
- Excalibur™ FPGA
- Enhanced configuration devices

Table 1. Stratix II Devices

Device	Package	Pins
EP2S15	Flip Chip FBGA	484
	Flip Chip FBGA	672
EP2S30	Flip Chip FBGA	484
	Flip Chip FBGA	672
EP2S60	Flip Chip FBGA	484
	Flip Chip FBGA	672
	Flip Chip FBGA	1,020
EP2S90	Flip Chip FBGA	484
	Flip Chip FBGA	780
	Flip Chip FBGA	1,020
	Flip Chip FBGA	1,508
EP2S130	Flip Chip FBGA	780
	Flip Chip FBGA	1,020
	Flip Chip FBGA	1,508
EP2S180	Flip Chip FBGA	1,020
	Flip Chip FBGA	1,508

Table 2. Stratix II GX Devices

Device	Package	Pins
EP2SGX30	Flip Chip FBGA	780
EP2SGX60	Flip Chip FBGA	780
	Flip Chip FBGA	1152
EP2SGX90	Flip Chip FBGA	1152
	Flip Chip FBGA	1508
EP2SGX130	Flip Chip FBGA	1508

Table 3. Stratix GX Devices

Device	Package	Pins
EP1SGX10C	Flip Chip FBGA	672
EP1SGX10D	Flip Chip FBGA	672
EP1SGX25C	Flip Chip FBGA	672

Table 3. Stratix GX Devices (Continued)

Device	Package	Pins
EP1SGX25D	Flip Chip FBGA	672
	Flip Chip FBGA	1,020
EP1SGX25F	Flip Chip FBGA	1,020
EP1SGX40D	Flip Chip FBGA	1,020
EP1SGX40G	Flip Chip FBGA	1,020

Table 4. Stratix Devices

Device	Package	Pins
EP1S10	Flip Chip FBGA	484
	BGA, Wirebond	672
	FBGA, Wirebond (Option 2)	672
	Flip Chip FBGA	780
EP1S20	Flip Chip FBGA	484
	BGA, Wirebond	672
	FBGA, Wirebond (Option 2)	672
	Flip Chip FBGA	780
EP1S25	BGA, Wirebond	672
	FBGA, Wirebond (Option 2)	672
	Flip Chip FBGA	780
	Flip Chip FBGA	1,020
EP1S30	Flip Chip FBGA	780
	Flip Chip BGA	956
	Flip Chip FBGA	1,020
EP1S40	Flip Chip BGA	956
	Flip Chip FBGA	780
	Flip Chip FBGA	1,020
	Flip Chip FBGA	1,508
EP1S60	Flip Chip BGA	956
	Flip Chip FBGA	1,020
	Flip Chip FBGA	1,508
EP1S80	Flip Chip BGA	956
	Flip Chip FBGA	1,020
	Flip Chip FBGA	1,508

Table 5. Cyclone II Devices

Device	Package	Pins
EP2C5	TQFP, Wirebond	144
	PQFP, Wirebond	208
	FBGA, Wirebond (Option 2)	256
EP2C8	TQFP, Wirebond	144
	PQFP, Wirebond	208
	FBGA, Wirebond (Option 2)	256
EP2C20	PQFP, Wirebond	240
	FBGA, Wirebond (Option 2)	256
	FBGA, Wirebond (Option 3)	484
EP2C35	FBGA, Wirebond (Option 3)	484
	UBGA, Wirebond	484
	FBGA, Wirebond (Option 3)	672
EP2C50	FBGA, Wirebond (Option 3)	484
	UBGA, Wirebond	484
	FBGA, Wirebond (Option 3)	672
EP2C70	FBGA, Wirebond (Option 3)	672
	FBGA, Wirebond	896

Table 6. Cyclone Devices

Device	Package	Pins
EP1C3	TQFP, Wirebond	100
	TQFP, Wirebond	144
EP1C4	FBGA, Wirebond	324
	FBGA, Wirebond	400
EP1C6	TQFP, Wirebond	144
	PQFP, Wirebond	240
	FBGA, Wirebond (Option 1)	256
EP1C12	PQFP, Wirebond	240
	FBGA, Wirebond (Option 1)	256
	FBGA, Wirebond	324
EP1C20	FBGA, Wirebond	324
	FBGA, Wirebond	400

Table 7. MAX Series Devices

Device	Package	Pins
MAX II Devices		
EPM240	TQFP, Wirebond	100
	FBGA, Wirebond (Option 2)	100
	MBGA, Wirebond	100
EPM570	TQFP, Wirebond	100
	TQFP, Wirebond	144
	MBGA, Wirebond	100
	FBGA, Wirebond (Option 2)	100
	FBGA, Wirebond (Option 1)	256
	MBGA, Wirebond	256
	MBGA, Wirebond	256
EPM1270	TQFP, Wirebond	144
	FBGA, Wirebond (Option 1)	256
	MBGA, Wirebond	256
EPM2210	FBGA, Wirebond (Option 1)	256
	FBGA, Wirebond	324
MAX 9000 Devices		
EPM9320	BGA, Wirebond	356
EPM9320A	BGA, Wirebond	356
EPM9560	BGA, Wirebond	356
MAX 7000B Devices		
EPM7032B	PLCC, Wirebond	44
	PQFP, Wirebond	44
	TQFP, Wirebond	44
	UBGA, Wirebond	49
EPM7064B	TQFP, Wirebond	44
	UBGA, Wirebond	49
	FBGA, Wirebond	100
	TQFP, Wirebond	100

Table 7. MAX Series Devices (Continued)

Device	Package	Pins
EPM7128B	UBGA, Wirebond	49
	TQFP, Wirebond	100
	FBGA, Wirebond	100
	TQFP, Wirebond	144
	UBGA, Wirebond	169
	FBGA, Wirebond (Option 1)	256
EPM7256B	TQFP, Wirebond	100
	TQFP, Wirebond	144
	UBGA, Wirebond	169
	PQFP, Wirebond	208
	FBGA, Wirebond (Option 1)	256
EPM7512B	TQFP, Wirebond	144
	UBGA, Wirebond	169
	PQFP, Wirebond	208
	FBGA, Wirebond (Option 1)	256
	BGA, Wirebond (Option 1)	256
MAX 7000AE Devices		
EPM7032AE	PLCC, Wirebond	44
	TQFP, Wirebond	44
EPM7064AE	PLCC, Wirebond	44
	TQFP, Wirebond	100
	TQFP, Wirebond	144
	UBGA, Wirebond	49
	FBGA, Wirebond	100
	FBGA, Wirebond (Option 1)	256
EPM7128AE	PLCC, Wirebond	84
	TQFP, Wirebond	100
	FBGA, Wirebond	100
	UBGA, Wirebond	169
	TQFP, Wirebond	144
	FBGA, Wirebond (Option 1)	256

Table 7. MAX Series Devices (Continued)

Device	Package	Pins
EPM7256AE	TQFP, Wirebond	100
	FBGA, Wirebond	100
	TQFP, Wirebond	144
	PQFP, Wirebond	208
	FBGA, Wirebond (Option 1)	256
EPM7512AE	TQFP, Wirebond	144
	PQFP, Wirebond	208
	BGA, Wirebond (Option 1)	256
	FBGA, Wirebond (Option 1)	256
MAX 7000A Devices		
EPM7032A	PLCC, Wirebond	44
	TQFP, Wirebond	44
EPM7128A	PLCC, Wirebond	84
	TQFP, Wirebond	100
	FBGA, Wirebond	100
	TQFP, Wirebond	144
	FBGA, Wirebond (Option 1)	256
EPM7256A	TQFP, Wirebond	100
	TQFP, Wirebond	144
	PQFP, Wirebond	208
	FBGA, Wirebond (Option 1)	256

Table 8. HardCopy Series Devices

Device	Package	Pins
HC20K400	BGA, Wirebond (Option 3)	652
HC20K600	BGA, Wirebond (Option 3)	652
	Flip Chip FBGA	672
HC220	Flip Chip FPGA	672
	Flip Chip FBGA	780
HC230	Flip Chip FPGA	1020
HC1S25	FBGA, Wirebond (Option 3)	672
	BGA, Wirebond	672

Table 8. HardCopy Series Devices (Continued)

Device	Package	Pins
HC1S30	Flip Chip FBGA	780
HC1S40	Flip Chip FBGA	780
HC1S60	Flip Chip FBGA	1,020
HC1S80	Flip Chip FBGA	1,020

Table 9. APEX Series Devices

Device	Package	Pins
APEX II Devices		
EP2A15	Flip Chip FBGA	672
	Flip Chip BGA	724
EP2A25	Flip Chip FBGA	672
	Flip Chip BGA	724
	Flip Chip FBGA	1,020
EP2A40	Flip Chip FBGA	672
	Flip Chip BGA	724
	Flip Chip FBGA	1,020
EP2A70	Flip Chip BGA	724
	Flip Chip FBGA	1,508
APEX 20KE Devices		
EP20K30E	TQFP, Wirebond	144
	FBGA, Wirebond	144
	PQFP, Wirebond	208
	FBGA, Wirebond	324
EP20K60E	TQFP, Wirebond	144
	FBGA, Wirebond	144
	PQFP, Wirebond	208
	PQFP, Wirebond	240
	FBGA, Wirebond	324
	BGA, Wirebond	356

Table 9. APEX Series Devices (Continued)

Device	Package	Pins
EP20K100E	TQFP, Wirebond	144
	FBGA, Wirebond	144
	PQFP, Wirebond	208
	PQFP, Wirebond	240
	FBGA, Wirebond	324
	BGA, Wirebond	356
EP20K160E	TQFP, Wirebond	144
	PQFP, Wirebond	208
	PQFP, Wirebond	240
	BGA, Wirebond	356
	FBGA, Wirebond (Option 2)	484
EP20K200E	PQFP, Wirebond	208
	PQFP, Wirebond	240
	BGA, Wirebond	356
	FBGA, Wirebond (Option 2)	484
	BGA, Wirebond (Option 2)	652
	FBGA, Wirebond (Option 2)	672
EP20K300E	PQFP, Wirebond	240
	BGA, Wirebond (Option 2)	652
	FBGA, Wirebond (Option 2)	672
EP20K400E	BGA, Wirebond (Option 3)	652
	Flip Chip FBGA	672
EP20K600E	BGA, Wirebond (Option 3)	652
	Flip Chip FBGA	672
	Flip Chip FBGA	1,020
EP20K1000E	Flip Chip BGA	652
	Flip Chip FBGA	672
	Flip Chip FBGA	1,020
EP20K1500E	Flip Chip BGA	652
	Flip Chip FBGA	1,020
APEX 20KC Devices		

Table 9. APEX Series Devices (Continued)

Device	Package	Pins
EP20K200C	PQFP, Wirebond	208
	PQFP, Wirebond	240
	BGA, Wirebond	356
	FBGA, Wirebond (Option 2)	484
EP20K400C	BGA, Wirebond (Option 3)	652
	Flip Chip FBGA	672
EP20K600C	BGA, Wirebond (Option 3)	652
	Flip Chip FBGA	672
	Flip Chip FBGA	1,020
EP20K1000C	Flip Chip BGA	652
	Flip Chip FBGA	672
	Flip Chip FBGA	1,020

APEX 20K Devices		
EP20K100	TQFP, Wirebond	144
	PQFP, Wirebond	208
	PQFP, Wirebond	240
	FBGA, Wirebond	324
	BGA, Wirebond	356
EP20K160	PQFP, Wirebond	240
	TQFP, Wirebond	144
EP20K200	PQFP, Wirebond	208
	PQFP, Wirebond	240
	BGA, Wirebond	356
	FBGA, Wirebond (Option 2)	484
EP20K300	FBGA, Wirebond (Option 2)	672
EP20K400	BGA, Wirebond (Option 3)	652
	PGA, Wirebond	655
	Flip Chip FBGA	672

Table 10. ACEX 1K Devices

Device	Package	Pins
EP1K10	TQFP, Wirebond	100
	TQFP, Wirebond	144
	PQFP, Wirebond	208
	FBGA, Wirebond (Option 1)	256
EP1K30	TQFP, Wirebond	144
	PQFP, Wirebond	208
	FBGA, Wirebond (Option 1)	256
EP1K50	TQFP, Wirebond	144
	PQFP, Wirebond	208
	FBGA, Wirebond (Option 1)	256
	FBGA, Wirebond (Option 2)	484
EP1K100	PQFP, Wirebond	208
	FBGA, Wirebond (Option 1)	256
	FBGA, Wirebond (Option 2)	484

Table 11. Mercury Devices

Device	Package	Pins
EP1M120	Flip Chip FBGA	484
EP1M350	Flip Chip FBGA	780

Table 12. FLEX Series Devices

Device	Package	Pins
FLEX 10KA Devices		
EPF10K10A	TQFP, Wirebond	100
	TQFP, Wirebond	144
	PQFP, Wirebond	208
	FBGA, Wirebond (Option 1)	256

Table 12. FLEX Series Devices (Continued)		
Device	Package	Pins
EPF10K30A	TQFP, Wirebond	144
	PQFP, Wirebond	208
	PQFP, Wirebond	240
	FBGA, Wirebond (Option 1)	256
	BGA, Wirebond	356
	FBGA, Wirebond (Option 2)	484
EPF10K100A	RQFP, Wirebond	240
	BGA, Wirebond	356
	FBGA, Wirebond (Option 2)	484
	BGA, Wirebond	600
EPF10K250A	PGA, Wirebond	599
	BGA, Wirebond	600
FLEX 10KS Devices		
EPF10K50S	TQFP, Wirebond	144
	PQFP, Wirebond	208
	PQFP, Wirebond	240
	FBGA, Wirebond (Option 1)	256
	BGA, Wirebond	356
	FBGA, Wirebond (Option 2)	484
EPF10K200S	RQFP, Wirebond	240
	BGA, Wirebond	356
	FBGA, Wirebond (Option 2)	484
	BGA, Wirebond	600
	FBGA, Wirebond (Option 2)	672
FLEX 10KE Devices		
EPF10K30E	TQFP, Wirebond	144
	PQFP, Wirebond	208
	FBGA, Wirebond (Option 1)	256
	FBGA, Wirebond (Option 2)	484

Table 12. FLEX Series Devices (Continued)

Device	Package	Pins
EPF10K50E	TQFP, Wirebond	144
	PQFP, Wirebond	208
	PQFP, Wirebond	240
	FBGA, Wirebond (Option 1)	256
	BGA, Wirebond	356
	FBGA, Wirebond (Option 2)	484
EPF10K100E	PQFP, Wirebond	208
	PQFP, Wirebond	240
	FBGA, Wirebond (Option 1)	256
	BGA, Wirebond	356
	FBGA, Wirebond (Option 2)	484
EPF10K130E	PQFP, Wirebond	240
	BGA, Wirebond	356
	FBGA, Wirebond (Option 2)	484
	BGA, Wirebond	600
	FBGA, Wirebond (Option 2)	672
EPF10K200E	PGA, Wirebond	599
	BGA, Wirebond	600
	FBGA, Wirebond (Option 2)	672
FLEX Devices		
EPF10K10	PLCC, Wirebond	84
	TQFP, Wirebond	144
	PQFP, Wirebond	208
EPF10K20	TQFP, Wirebond	144
	RQFP, Wirebond	208
	RQFP, Wirebond	240
EPF10K30	RQFP, Wirebond	208
	RQFP, Wirebond	240
	BGA, Wirebond	356

Table 12. FLEX Series Devices (Continued)		
Device	Package	Pins
EPF10K40	RQFP, Wirebond	208
	RQFP, Wirebond	240
EPF10K50	RQFP, Wirebond	240
	BGA, Wirebond	356
	PGA, Wirebond	403
EPF10K50V	RQFP, Wirebond	240
	PQFP, Wirebond	240
	BGA, Wirebond	356
	FBGA, Wirebond	484
EPF10K70	RQFP, Wirebond	240
	PGA, Wirebond	503
EPF10K100	PGA, Wirebond	503
EPF10K130V	PGA, Wirebond	599
	BGA, Wirebond	600
EPF6010A	TQFP, Wirebond	100
	TQFP, Wirebond	144
	PQFP, Wirebond	208
EPF6016	TQFP, Wirebond	144
	PQFP, Wirebond	208
	PQFP, Wirebond	240
	BGA, Wirebond (Option 2)	256
EPF6016A	TQFP, Wirebond	100
	FBGA, Wirebond	100
	TQFP, Wirebond	144
	PQFP, Wirebond	208
	FBGA, Wirebond (Option 1)	256
EPF6024A	TQFP, Wirebond	144
	PQFP, Wirebond	208
	PQFP, Wirebond	240
	BGA, Wirebond (Option 2)	256
	FBGA, Wirebond (Option 1)	256
EPF8282A	PLCC, Wirebond	84
	TQFP, Wirebond	100

Table 12. FLEX Series Devices (Continued)

Device	Package	Pins
EPF8452A	TQFP, Wirebond	100
	PQFP, Wirebond	160

Table 13. Excalibur Devices

Device	Package	Pins
EPXA1	FBGA, Wirebond (Option 2)	484
	Flip Chip FBGA	672
EPXA4	Flip Chip FBGA	672
	Flip Chip FBGA	1,020
EPXA10	Flip Chip FBGA	1,020

Table 14. Enhanced Configuration Devices

Device	Package	Pins
EPC1	PDIP, Wirebond	8
	PLCC, Wirebond	20
EPC2	PLCC, Wirebond	20
	TQFP, Wirebond	32
EPC4	PLCC, Wirebond	44
	TQFP, Wirebond	44
	PQFP, Wirebond	100
	FPGA, Wirebond	144
EPC8	PQFP, Wirebond (Option 2)	100
EPC16	UBGA, Wirebond	88
	PQFP, Wirebond (Option 2)	100
EPC32	FPGA, Wirebond	88
EPC1441	PDIP, Wirebond	8
	PLCC, Wirebond	20
	TQFP, Wirebond	32

Thermal Resistance

Table 15 through 34 provide θ_{JA} (junction-to-ambient thermal resistance) and θ_{JC} (junction-to-case thermal resistance) values for the following Altera device families:

- Stratix series FPGAs
- Cyclone series FPGAs
- MAX series CPLDs
- HardCopy series Structured ASICs
- APEX series FPGAs
- ACEX 1K FPGAs
- Mercury FPGAs
- FLEX series FPGAs
- Excalibur FPGA
- Classic devices

Altera is transitioning to an industry-standard copper lid for its thermally enhanced BGA and thermally enhanced Flip Chip FBGA package offerings (as mentioned in the *Process Change Notice PCN024* available on Altera's website: <http://www.altera.com/literature/pcn/pcn0214.pdf>). This change affects the APEX 20KE, APEX 20KC, APEX II, Mercury, and Excalibur device families. Therefore, two thermal resistance specifications are provided for devices affected by this change. The older packages are identified as using the aluminum silicon carbide (AlSiC) lid, while the newer packages are identified as using the copper (Cu) lid.

Thermally enhanced BGA and thermally enhanced Flip Chip FBGA packages offered in the newer Altera families, including Stratix and Stratix GX, were introduced using an industry-standard Cu lid. Therefore, these device specifications include only a single thermal resistance specification.

Table 15. Thermal Resistance of Stratix II Devices

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EP2S15	484	Flip Chip FBGA	0.36	13.1	11.1	9.6	8.3
	672	Flip Chip FBGA	0.36	12.2	10.2	8.8	7.6
EP2S30	484	Flip Chip FBGA	0.21	12.6	10.6	9.1	7.9
	672	Flip Chip FBGA	0.21	11.7	9.7	8.3	7.1
EP2S60	484	Flip Chip FBGA	0.13	12.3	10.3	8.8	7.5
	672	Flip Chip FBGA	0.13	11.4	9.4	7.8	6.7
	1,020	Flip Chip FBGA	0.13	10.4	8.4	7.0	5.9

Table 15. Thermal Resistance of Stratix II Devices (Continued)

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EP2S90	484	Flip Chip HBGA	0.07	12.0	9.9	8.3	7.1
	780	Flip Chip FBGA	0.09	10.80	8.8	7.3	6.1
	1,020	Flip Chip FBGA	0.10	10.2	8.2	6.8	5.7
	1,508	Flip Chip FBGA	0.10	9.3	7.4	6.1	5
EP2S130	780	Flip Chip FBGA	0.07	10.1	8.7	7.2	6.0
	1,020	Flip Chip FBGA	0.07	9.5	8.1	6.7	5.5
	1,508	Flip Chip FBGA	0.07	8.6	7.3	6.0	4.8
EP2S180	1,020	Flip Chip FBGA	0.05	9	7.9	6.5	5.4
	1,508	Flip Chip FBGA	0.05	8.1	7.1	5.8	4.7

Table 16. Thermal Resistance of Stratix II GX Devices

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EP2SGX30	780	Flip Chip FBGA	0.24	11.1	8.6	7.2	6
EP2SGX60	780	Flip Chip FBGA	0.15	10.9	8.4	6.9	5.8
	1152	Flip Chip FBGA	0.15	9.9	7.5	6.1	5
EP2SGX90	1152	Flip Chip FBGA	0.11	9.6	7.3	5.9	4.9
	1508	Flip Chip FBGA	0.11	9	6.7	5.4	4.4
EP2SGX130	1508	Flip Chip FBGA	0.1	8.3	6.6	5.3	4.3

Table 17. Thermal Resistance of Stratix GX Devices

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EP1SGX10C EP1SGX10D	672	Flip Chip FBGA	0.39	11.1	9.1	7.7	6.5
EP1SGX25C EP1SGX25D	672	Flip Chip FBGA	0.23	10.8	8.8	7.4	6.2
EP1SGX25D EP1SGX25F	1020	Flip Chip FBGA	0.23	9.9	7.9	6.5	5.4
EP1SGX40D EP1SGX40G	1020	Flip Chip FBGA	0.16	9.8	7.7	6.4	5.3

Table 18. Thermal Resistance of Stratix Devices

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EP1S10	484	Flip Chip FBGA	0.38	11.9	9.8	8.4	7.2
	672	BGA	3.2	16.8	13.7	11.9	10.5
	672	FBGA	3.4	17.2	14	12.2	10.8
	780	Flip Chip FBGA	0.43	10.9	8.8	7.4	6.3
EP1S20	484	Flip Chip FBGA	0.30	11.8	9.7	8.3	7.1
	672	BGA	2.5	15.5	12.4	10.7	9.3
	672	FBGA	2.7	16	12.8	11	9.6
	780	Flip Chip FBGA	0.31	10.7	8.6	7.2	6.1
EP1S25	672	BGA	2.2	14.8	11.7	10.0	8.7
	672	FBGA	2.3	15.3	12	10.4	9
	780	Flip Chip FBGA	0.25	10.5	8.5	7.1	6.0
	1020	Flip Chip FBGA	0.25	10.0	8.0	6.6	5.5
EP1S30	780	Flip Chip FBGA	0.2	10.4	8.4	7.0	5.9
	956	Flip Chip BGA	0.2	9.1	7.1	5.8	4.8
	1020	Flip Chip FBGA	0.2	9.9	7.9	6.5	5.4
EP1S40	780	Flip Chip FBGA	0.17	10.4	8.3	6.9	5.8
	956	Flip Chip BGA	0.18	9.0	7.0	5.7	4.7
	1020	Flip Chip FBGA	0.17	9.8	7.8	6.4	5.3
	1508	Flip Chip FBGA	0.18	9.1	7.1	5.8	4.7
EP1S60	956	Flip Chip BGA	0.13	8.9	6.9	5.6	4.6
	1020	Flip Chip FBGA	0.13	9.7	7.7	6.3	5.2
	1508	Flip Chip FBGA	0.13	8.9	7.0	5.6	4.6
EP1S80	956	Flip Chip BGA	0.1	8.8	6.8	5.5	4.5
	1020	Flip Chip FBGA	0.1	9.6	7.6	6.2	5.1
	1508	Flip Chip FBGA	0.1	8.8	6.9	5.5	4.5

Table 19. Thermal Resistance of Cyclone II Devices

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EP2C5	144	TQFP	10	31	29.3	27.9	25.5
	208	PQFP	5.5	30.4	29.2	27.3	22.3
	256	FBGA	8.7	30.2	26.1	23.6	21.7
EP2C8	144	TQFP	9.9	29.8	28.3	26.9	24.9
	208	PQFP	5.4	30.2	28.8	26.9	21.7
	256	FBGA	7.1	27	23	20.5	18.5
EP2C20	240	PQFP	4.2	26.6	24	21.4	17.4
	256	FBGA	5.5	24.2	20	17.8	16
	484	FBGA	4.2	21	17	14.8	13.1
EP2C35	484	FBGA	3.3	19.4	15.4	13.3	11.7
	484	UBGA	5.0	20.6	16.6	14.5	12.8
	672	FBGA	3.1	18.6	14.6	12.6	11.1
EP2C50	484	FBGA	2.8	18.4	14.4	12.4	10.9
	484	UBGA	4.4	19.6	15.6	13.6	11.9
	672	FBGA	2.6	17.7	13.7	11.8	10.2
EP2C70	672	FBGA	2.2	16.9	13	11.1	9.7
	896	FBGA	2.1	16.3	11.9	10.5	9.1

Table 20. Thermal Resistance of Cyclone Devices

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EP1C3	100	TQFP	11.0	37.5	35.4	33.4	29.8
	144	TQFP	10.0	31.1	29.4	27.9	25.5
EP1C6	144	TQFP	9.8	29.4	28.0	26.7	24.7
	240	PQFP	4.3	27.2	24.7	22.1	17.8
	256	FBGA	8.8	28.7	24.5	22.3	20.5
EP1C12	240	PQFP	4.0	26.0	23.4	20.8	17.1
	256	FBGA	6.6	24.3	20.2	18.1	16.4
	324	FBGA	6.1	23.0	19.8	17.7	16.1
EP1C20	324	FBGA	5.0	21.0	17.7	15.6	14.1
	400	FBGA	4.7	20.7	17.5	15.5	13.9

Table 21. Thermal Resistance of MAX II Devices

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EPM240	100	TQFP	12.0	39.5	37.5	35.5	31.6
	100	MBGA	32.1	53.8	47.7	45.7	44.0
	100	FBGA	20.8	51.2	45.2	43.2	41.5
EPM570	100	TQFP	11.2	38.7	36.6	34.6	30.8
	100	MBGA	25.0	46.5	40.4	38.4	36.8
	100	FBGA	14.8	42.8	36.8	34.9	33.3
	144	TQFP	10.5	32.1	30.3	28.7	26.1
	256	FBGA	13.0	37.4	33.1	30.5	28.4
	256	MBGA	12.9	39.5	33.6	31.6	30.1
	256	MBGA	12.9	39.5	33.6	31.6	30.1
EPM1270	144	TQFP	10.5	31.4	29.7	28.2	25.8
	256	FBGA	10.4	33.5	29.3	26.8	24.7
	256	MBGA	10.6	36.1	30.2	28.3	26.8
EPM2210	256	FBGA	8.7	30.2	26.1	23.6	21.7
	324	FBGA	8.2	29.8	25.7	23.3	21.3

Table 22. Thermal Resistance of MAX 9000 Devices

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EPM9320	84	PLCC	9.0	29.0	27.0	25.0	23.0
	208	RQFP	1.0	17.0	16.0	15.0	13.0
	280	PGA	2.0	14.0	10.0	7.0	5.0
	356	BGA	2.0	14.0	12.0	11.0	10.0
EPM9320A	84	PLCC	9.0	29.0	27.0	26.0	23.0
	208	RQFP	2.0	17.0	16.0	15.0	13.0
	356	BGA	1.0	12.0	11.0	10.0	9.0
EPM9400	84	PLCC	9.0	29.0	27.0	25.0	23.0
	208	RQFP	1.0	17.0	16.0	15.0	13.0
	240	RQFP	1.0	14.0	12.0	11.0	10.0
EPM9480	208	RQFP	1.0	17.0	16.0	15.0	12.0
	240	RQFP	1.0	12.0	11.0	10.0	9.0

Table 22. Thermal Resistance of MAX 9000 Devices (Continued)

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EPM9560	208	RQFP	1.0	17.0	16.0	15.0	12.0
	240	RQFP	1.0	12.0	11.0	10.0	9.0
	280	PGA	2.0	14.0	10.0	7.0	5.0
	304	RQFP	1.0	12.0	11.0	10.0	9.0
	356	BGA	1.0	12.0	11.0	10.0	9.0
EPM9560A	208	RQFP	1.0	17.0	16.0	15.0	12.0
	240	RQFP	1.0	11.0	10.0	9.0	8.0
	356	BGA	1.0	12.0	11.0	10.0	9.0

Table 23. Thermal Resistance of MAX 7000 Devices

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EPM7032	44	PLCC	10.0	33.0	31.0	30.0	27.0
		PQFP	15.0	48.0	46.0	45.0	42.0
		TQFP	14.0	46.0	44.0	43.0	40.0
EPM7032B	44	PLCC	10.0	33.0	31.0	30.0	27.0
		TQFP	14.0	46.0	44.0	43.0	40.0
	49	UBGA	23.0	69.0	67.0	66.0	62.0
EPM7032S	44	PLCC	10.0	33.0	31.0	30.0	27.0
		TQFP	14.0	46.0	44.0	43.0	40.0
EPM7032V	44	PLCC	9.0	31.0	30.0	28.0	25.0
		TQFP	14.0	45.0	44.0	42.0	39.0
EPM7032AE	44	PLCC	9.0	31.0	30.0	28.0	25.0
		TQFP	14.0	46.0	45.0	43.0	40.0
EPM7064S	44	PLCC	9.0	31.0	30.0	28.0	25.0
		TQFP	14.0	46.0	44.0	43.0	40.0
	84	PLCC	9.0	28.0	26.0	25.0	23.0
	100	TQFP	11.0	39.0	37.0	35.0	32.0

Table 23. Thermal Resistance of MAX 7000 Devices (Continued)

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EPM7064	44	PLCC	9.0	31.0	30.0	28.0	25.0
		TQFP	13.0	44.0	43.0	41.0	38.0
	68	PLCC	9.0	29.0	28.0	26.0	23.0
	84	PLCC	9.0	28.0	26.0	25.0	22.0
	100	PQFP	6.0	33.0	32.0	31.0	30.0
EPM7064AE EPM7064B	44	PLCC	9.0	31.0	30.0	28.0	25.0
		TQFP	14.0	46.0	45.0	43.0	40.0
	49	UBGA	23.0	56.0	53.0	51.0	47.0
	100	TQFP	12.0	39.0	37.0	35.0	31.0
		FBGA	21.0	49.0	47.0	44.0	40.0
EPM7096	68	PLCC	9.0	29.0	27.0	26.0	23.0
	84	PLCC	9.0	28.0	26.0	24.0	22.0
	100	PQFP	6.0	32.0	31.0	30.0	29.0
EPM7128A	84	PLCC	9.0	28.0	26.0	25.0	22.0
	100	TQFP	11.0	37.0	35.0	33.0	30.0
		FBGA	18.0	44.0	42.0	39.0	35.0
	144	TQFP	9.0	31.0	29.0	28.0	25.0
	256	FBGA	12.0	38.0	36.0	34.0	31.0
EPM7128B	49	UBGA	22.0	53.0	50.0	48.0	44.0
	100	TQFP	11.0	38.0	36.0	34.0	31.0
		FBGA	19.0	46.0	44.0	41.0	37.0
	144	TQFP	9.0	32.0	30.0	29.0	26.0
	169	UBGA	16.0	44.0	42.0	39.0	35.0
	256	FBGA	13.0	40.0	38.0	36.0	33.0
EPM7128E	84	PLCC	10.0	29.0	28.0	26.0	23.0
	100	PQFP	6.0	32.0	31.0	30.0	29.0
	160	PQFP	6.0	32.0	31.0	30.0	28.0
EPM7128S	84	PLCC	10.0	30.0	28.0	26.0	23.0
	100	TQFP	12.0	38.0	36.0	34.0	30.0
		PQFP	10.0	35.0	34.0	33.0	32.0
	160	PQFP	7.0	33.0	32.0	31.0	30.0

Table 23. Thermal Resistance of MAX 7000 Devices (Continued)

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EPM7128AE	84	PLCC	11.0	30.0	28.0	26.0	23.0
	100	TQFP	12.0	38.0	36.0	34.0	30.0
		FBGA	14.0	43.0	40.0	38.0	37.0
	144	TQFP	11.0	33.0	30.0	28.0	26.0
	169	UBGA	14.0	42.0	40.0	38.0	36.0
	256	FBGA	12.0	39.0	37.0	35.0	31.0
EPM7160E	84	PLCC	10.0	29.0	28.0	26.0	23.0
	100	PQFP	6.0	32.0	31.0	30.0	29.0
	160	PQFP	6.0	33.0	32.0	31.0	30.0
EPM7160S	84	PLCC	10.0	35.0	28.0	26.0	23.0
	100	TQFP	12.0	37.0	35.0	33.0	30.0
	160	PQFP	6.0	33.0	32.0	31.0	30.0
EPM7192S	160	PQFP	6.0	32.0	31.0	30.0	29.0
EPM7192E	160	PGA	6.0	20.0	13.0	10.0	8.0
		PQFP	6.0	32.0	31.0	30.0	26.0
EPM7256A	100	TQFP	9.0	36.0	34.0	32.0	30.0
	144	TQFP	8.0	32.0	27.0	25.0	24.0
	208	PQFP	5.0	30.0	28.0	26.0	21.0
	256	FBGA	12.0	34.0	32.0	29.0	28.0
EPM7256B	100	TQFP	12.0	37.0	35.0	33.0	30.0
	144	TQFP	9.0	33.0	29.0	27.0	25.0
	169	UBGA	13.0	40.0	38.0	36.0	34.0
	208	PQFP	5.0	31.0	29.0	27.0	22.0
	256	FBGA	9.0	34.0	32.0	30.0	28.0
EPM7256E	192	PGA	6.0	20.0	13.0	10.0	8.0
	160	PQFP	6.0	31.0	30.0	29.0	25.0
	208	RQFP	1.0	17.0	16.0	15.0	13.0
EPM7256S	208	PQFP	5.0	30.0	29.0	26.0	21.0
		RQFP	1.0	18.0	17.0	16.0	15.0

Table 23. Thermal Resistance of MAX 7000 Devices (Continued)

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EPM7256AE	100	FBGA	13.0	42.0	39.0	37.0	36.0
	100	TQFP	12.0	37.0	35.0	33.0	30.0
	144	TQFP	9.0	33.0	29.0	27.0	25.0
	208	PQFP	5.0	31.0	29.0	27.0	22.0
	256	FBGA	9.0	34.0	32.0	30.0	28.0
EPM7512AE	144	TQFP	10.0	32.0	27.0	25.0	23.0
	208	PQFP	5.0	30.0	28.0	25.0	21.0
	256	BGA	1.2	14.0	12.0	11.0	10.0
		FBGA	11.0	32.0	30.0	28.0	22.0
EPM7512B	144	TQFP	10.0	32.0	27.0	25.0	24.0
	169	UBGA	12.0	35.0	33.0	31.0	30.0
	208	PQFP	5.0	30.0	28.0	25.0	21.0
	256	BGA	1.2	14.0	12.0	11.0	10.0
	256	FBGA	11.0	32.0	30.0	28.0	27.0

Table 24. Thermal Resistance of MAX 3000A Devices

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EPM3032A	44	TQFP	14.0	46.0	45.0	43.0	40.0
		PLCC	9.0	31.0	30.0	28.0	25.0
EPM3064A	44	TQFP	14.0	46.0	45.0	43.0	40.0
		PLCC	9.0	31.0	30.0	28.0	25.0
	100	TQFP	12.0	39.0	37.0	35.0	31.0
EPM3128A	100	TQFP	12.0	38.0	36.0	34.0	30.0
	144	TQFP	11.0	33.0	30.0	28.0	26.0
EPM3256A	144	TQFP	9.0	33.0	29.0	27.0	25.0
	208	PQFP	5.0	31.0	29.0	27.0	22.0
EPM3512A	208	PQFP	5.0	30.0	28.0	25.0	21.0
	256	FBGA	11.0	32.0	30.0	28.0	22.0

Table 25. Thermal Resistance of HardCopy Series Devices

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
HC210	484	Flip Chip FBGA	0.8	13.4	11.2	9.6	8.3
	484	FBGA	6.6	24.2	20.3	18.3	16.6
HC220	672	Flip Chip FBGA	0.5	12.1	9.9	8.3	7.1
	780	Flip Chip FBGA	0.5	11.7	9.5	8.0	6.8
HC230	1020	Flip Chip FBGA	0.3	10.8	8.6	7.1	6.0
HC240	1020	Flip Chip FBGA	0.2	10.6	8.4	6.9	5.8
	1508	Flip Chip FBGA	0.2	9.7	7.5	6.1	5.0
HC20K400	652	BGA	0.5	9.1	7.9	6.4	5.3
HC20K600	672	Flip Chip FBGA	0.96	13.0	10.2	8.6	7.3
HC1S25	672	FBGA	3.6	19.7	15.8	13.9	12.4
		BGA	3.4	19.3	15.6	13.8	12.3
HC1S30	780	Flip Chip FBGA	0.43	10.9	8.8	7.4	6.3
HC1S40	780	Flip Chip FBGA	0.43	10.9	8.8	7.4	6.3
HC1S60	1020	Flip Chip FBGA	0.291	12.22	8.54	7.02	5.82
HC1S80	1020	Flip Chip FBGA	0.291	12.22	8.54	7.02	5.82

Table 26. Thermal Resistance of APEX II Devices

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EP2A15	672	Flip Chip FBGA (Cu lid)	0.22	10.8	8.8	7.4	6.2
		Flip Chip FBGA (AlSiC lid)	0.34	11.6	9.6	8.0	6.6
	724	Flip Chip BGA (Cu lid)	0.23	9.7	7.7	6.4	5.3
		Flip Chip BGA (AlSiC lid)	0.35	10.0	8.2	6.6	5.4
EP2A25	672	FBGA (Cu lid)	0.17	10.7	8.7	7.2	6.1
		Flip Chip FBGA (AlSiC lid)	0.26	11.5	9.6	8.0	6.6
	724	Flip Chip BGA (Cu lid)	0.17	9.6	7.6	6.2	5.2
		Flip Chip BGA (AlSiC lid)	0.27	10.0	8.2	6.6	5.4
	1020	Flip Chip FBGA (Cu lid)	0.17	9.8	7.8	6.4	5.3
		Flip Chip FBGA (AlSiC lid)	0.27	10.4	8.5	6.9	5.7

Table 26. Thermal Resistance of APEX II Devices (Continued)

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EP2A40	672	Flip Chip FBGA (Cu lid)	0.24	10.0	8.2	6.9	5.9
		Flip Chip FBGA (AlSiC lid)	0.2	10.0	8.2	6.9	5.9
	724	Flip Chip BGA (Cu lid)	0.15	9.5	7.5	6.1	5.1
		Flip Chip BGA (AlSiC lid)	0.19	9.5	7.5	6.1	5.1
	1,020	Flip Chip FBGA (Cu lid)	0.15	9.7	7.7	6.3	5.2
		Flip Chip FBGA (AlSiC lid)	0.19	9.7	7.7	6.3	5.2
EP2A70	724	Flip Chip BGA (Cu lid)	0.10	9.3	7.3	6.0	4.9
		Flip Chip BGA (AlSiC lid)	0.14	10.0	7.9	6.4	5.3
	1,508	Flip Chip FBGA (Cu lid)	0.10	8.8	6.8	5.5	4.5
		Flip Chip FBGA (AlSiC lid)	0.14	9.3	7.3	5.8	4.7

Table 27. Thermal Resistance of APEX 20K & APEX 20KE Devices

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EP20K30E	144	TQFP	8.0	29.0	28.0	26.0	25.0
	208	PQFP	5.0	30.0	29.0	27.0	22.0
	144	FBGA	14.0	36.0	34.0	32.0	29.0
	324	FBGA	9.0	31.0	29.0	28.0	25.0
EP20K60E	144	TQFP	7.0	28.0	26.0	25.0	24.0
	144	FBGA	11.0	33.0	32.0	30.0	27.0
	208	PQFP	5.0	30.0	28.0	26.0	21.0
	240	PQFP	4.0	26.0	24.0	21.0	17.0
	324	FBGA	7.0	29.0	28.0	26.0	24.0
	356	BGA	1.0	12.0	11.0	10.0	9.0
EP20K100	144	TQFP	7.0	26.0	25.0	24.0	23.0
	208	PQFP	5.0	29.0	27.0	25.0	20.0
	240	PQFP	4.0	25.0	23.0	20.0	17.0
	324	FBGA	6.0	28.0	26.0	25.0	23.0
	356	BGA	1.0	12.0	11.0	10.0	9.0

Table 27. Thermal Resistance of APEX 20K & APEX 20KE Devices (Continued)

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EP20K100E	144	TQFP	7.0	26.0	25.0	24.0	23.0
	144	FBGA	9.0	32.0	30.0	29.0	26.0
	208	PQFP	5.0	29.0	27.0	25.0	20.0
	240	PQFP	4.0	25.0	23.0	20.0	17.0
	324	FBGA	6.0	28.0	26.0	25.0	23.0
	356	BGA	1.0	12.0	11.0	10.0	9.0
EP20K160E	144	TQFP	6.0	25.0	24.0	23.0	22.0
	208	PQFP	5.0	28.0	26.0	23.0	19.0
	240	PQFP	4.0	24.0	21.0	19.0	16.0
	356	BGA	1.0	12.0	11.0	10.0	9.0
	484	FBGA	5.0	24.0	23.0	22.0	21.0
EP20K200	208	PQFP	4.0	25.0	23.0	20.0	17.0
	240	PQFP	3.0	21.0	19.0	17.0	15.0
	356	BGA	1.0	12.0	11.0	10.0	9.0
	484	FBGA	5.0	22.0	21.0	20.0	19.0
EP20K200E	208	PQFP	4.0	25.0	23.0	20.0	17.0
	240	PQFP	3.0	22.0	19.0	18.0	16.0
	356	BGA	2.0	12.0	11.0	10.0	9.0
	484	FBGA	5.0	23.0	22.0	21.0	20.0
	652	BGA	1.0	12.0	11.0	10.0	9.0
	672	FBGA	5.0	21.0	20.0	19.0	18.0
EP20K200C	208	PQFP	4.0	25.0	23.0	20.0	17.0
	240	PQFP	3.0	22.0	19.0	18.0	16.0
	356	BGA	2.0	12.0	11.0	10.0	9.0
	484	FBGA	5.0	23.0	22.0	21.0	20.0
EP20K300E	240	PQFP	3.0	19.0	18.0	16.0	15.0
	652	BGA	1.0	12.0	11.0	10.0	9.0
	672	FBGA	5.0	20.0	19.0	18.0	17.0
EP20K400	652	BGA	0.5	9.0	8.0	7.0	6.0
	655	PGA	1.0	8.0	7.0	6.0	4.0
	672	FBGA	0.36	11.6	9.6	7.9	6.5
	672	FBGA w/ fin (1)	0.5	7.0	4.0	3.0	2.6

Table 27. Thermal Resistance of APEX 20K & APEX 20KE Devices (Continued)

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EP20K400E EP20K400C	652	BGA	0.5	9.0	8.0	7.0	6.0
	672	FBGA (Cu lid)	0.25	10.9	8.8	7.4	6.3
		FBGA (AlSiC lid)	0.38	11.7	9.7	8.0	6.7
	672	FBGA w/ fin (1)	0.5	7.0	4.0	3.0	2.6
EP20K600E EP20K600C	652	BGA	0.5	9.0	8.0	7.0	6.0
	672	FBGA (Cu lid)	0.18	10.8	8.7	7.3	6.1
		FBGA (AlSiC lid)	0.28	11.6	9.6	7.9	6.5
	672	FBGA w/ fin (1)	0.5	5.0	3.0	3.0	2.0
	1,020	FBGA (Cu lid)	0.19	9.9	7.8	6.5	5.4
		FBGA (AlSiC lid)	0.29	10.4	8.4	6.8	5.6
	1,020	FBGA w/ fin (1)	0.5	5.0	3.0	3.0	2.0
EP20K1000E EP20K1000C	652	BGA (Cu lid)	0.12	8.3	7.0	5.6	4.5
		BGA (AlSiC lid)	0.2	9.3	7.4	6.0	4.9
	652	FBGA w/ fin (1)	0.5	4.0	3.0	3.0	2.0
	672	FBGA (Cu lid)	0.12	10.6	8.6	7.2	6.0
		FBGA (AlSiC lid)	0.2	11.4	9.4	7.7	6.3
	672	FBGA w/ fin (1)	0.5	6.0	4.0	3.0	2.0
	1,020	FBGA (Cu lid)	0.12	9.7	7.7	6.3	5.2
		FBGA (AlSiC lid)	0.19	10.2	8.2	6.6	5.4
	1,020	FBGA w/ fin (1)	0.5	5.0	3.0	2.0	2.0
EP20K1500E	652	BGA (Cu lid)	0.10	8.2	6.9	5.5	4.4
		BGA (AlSiC lid)	0.15	9.2	7.3	5.8	4.8
	652	FBGA	0.1	9.2	7.3	5.8	4.8
	652	FBGA w/ fin (1)	0.5	4.0	3.0	2.5	2.0
	1,020	FBGA (Cu lid)	0.10	9.6	7.6	6.2	5.1
		FBGA (AlSiC lid)	0.15	10.1	8.1	6.4	5.3
	1,020	FBGA w/ fin (1)	0.5	5.0	3.0	2.5	2.0

Note to Table 27:

- (1) “fin” is an extra heat sink that customers can add to the device. Several vendors make heat sinks, and they all have different sizes. Altera performed the thermal calculations in Table 27 using the following fin specifications: width: 0.25 mm; height: 7.0 mm; pitch: 1.5 mm; base thickness: 0.5 mm.

Table 28. Thermal Resistance of ACEX 1K Devices

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EP1K10	100	TQFP	11.0	37.0	35.0	33.0	29.0
	144	TQFP	8.0	31.0	29.0	28.0	25.0
	208	PQFP	6.0	30.0	29.0	27.0	22.0
	256	FBGA	12.0	37.0	35.0	33.0	30.0
EP1K30	144	TQFP	8.0	28.0	27.0	26.0	24.0
	208	PQFP	5.0	30.0	28.0	26.0	21.0
	256	FBGA	9.0	31.0	29.0	28.0	25.0
EP1K50	144	TQFP	7.0	26.0	25.0	24.0	23.0
	208	PQFP	5.0	29.0	28.0	25.0	20.0
	256	FBGA	7.0	30.0	28.0	27.0	24.0
	484	FBGA	5.0	25.0	24.0	23.0	22.0
EP1K100	208	PQFP	5.0	28.0	26.0	23.0	18.0
	256	FBGA	6.0	28.0	26.0	25.0	23.0
	484	FBGA	5.0	24.0	23.0	22.0	21.0

Table 29. Thermal Resistance of Mercury Devices

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EP1M120	484	FBGA (Cu lid)	0.58	12.2	10.1	8.7	7.5
	484	FBGA (AlSiC lid)	0.87	13.0	11.1	9.3	7.9
EP1M350	780	FBGA (Cu lid)	0.22	10.5	8.5	7.1	5.9
	780	FBGA (AlSiC lid)	0.34	11.0	9.2	7.6	6.3

Table 30. Thermal Resistance of FLEX 10K Devices

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EPF10K10	84	PLCC	9.0	28.0	26.0	24.0	22.0
	144	TQFP	7.0	26.0	25.0	24.0	23.0
	208	PQFP	5.0	29.0	27.0	25.0	20.0

Table 30. Thermal Resistance of FLEX 10K Devices (Continued)

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EPF10K10A	100	TQFP	10.0	35.0	33.0	31.0	28.0
	144	TQFP	7.0	29.0	28.0	26.0	25.0
	208	PQFP	5.0	30.0	29.0	27.0	21.0
	256	FBGA	7.0	33.0	30.0	28.0	26.0
EPF10K20	144	TQFP	6.0	24.0	23.0	22.0	21.0
	208	RQFP	1.0	17.0	16.0	15.0	13.0
	240	RQFP	1.0	14.0	12.0	11.0	10.0
EPF10K30	208	RQFP	1.0	17.0	16.0	15.0	12.0
	240	RQFP	1.0	13.0	12.0	11.0	10.0
	356	BGA	1.0	12.0	11.0	10.0	9.0
EPF10K30A	144	TQFP	7.0	25.0	24.0	23.0	22.0
	208	PQFP	5.0	29.0	27.0	24.0	19.0
	240	PQFP	4.0	25.0	22.0	20.0	17.0
	256	FBGA	6.0	28.0	26.0	24.0	23.0
	356	BGA	1.0	12.0	11.0	10.0	9.0
	484	FBGA	5.0	24.0	22.0	21.0	20.0
EPF10K30E	144	TQFP	9.0	28.0	27.0	26.0	24.0
	208	PQFP	5.0	30.0	28.0	26.0	21.0
	256	FBGA	9.0	31.0	29.0	28.0	25.0
	484	FBGA	6.0	26.0	25.0	24.0	22.0
EPF10K40	208	RQFP	1.0	17.0	16.0	15.0	12.0
	240	RQFP	1.0	13.0	12.0	11.0	10.0
EPF10K50	240	RQFP	1.0	12.0	11.0	10.0	9.0
	356	BGA	1.0	12.0	11.0	10.0	9.0
	403	PGA	3.0	12.0	10.0	9.0	8.0
		PGA (1)	3.0	10.0	8.0	7.0	6.0
EPF10K50V	240	PQFP	4.0	25.0	22.0	20.0	17.0
	240	RQFP	1.0	13.0	12.0	11.0	10.0
	356	BGA	1.0	12.0	11.0	10.0	9.0
	484	FBGA	5.0	23.0	22.0	21.0	20.0

Table 30. Thermal Resistance of FLEX 10K Devices (Continued)

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EPF10K50E	144	TQFP	9.0	26.0	25.0	24.0	23.0
	208	PQFP	5.0	29.0	27.0	24.0	19.0
	240	PQFP	4.0	25.0	22.0	20.0	17.0
	256	FBGA	6.0	29.0	27.0	26.0	24.0
	484	FBGA	5.0	25.0	24.0	23.0	21.0
EPF10K50S	144	TQFP	9.0	26.0	25.0	24.0	23.0
	208	PQFP	5.0	29.0	28.0	25.0	20.0
	240	PQFP	4.0	26.0	23.0	20.0	17.0
	256	FBGA	7.0	30.0	28.0	27.0	24.0
	356	BGA	1.0	12.0	11.0	10.0	9.0
	484	FBGA	5.0	25.0	24.0	23.0	22.0
EPF10K70	240	RQFP	1.0	12.0	11.0	10.0	9.0
	503	PGA	1.0	8.0	7.0	6.0	4.0
EPF10K100	503	PGA	1.0	8.0	7.0	6.0	4.0
		PGA (1)	1.0	6.0	5.0	4.0	3.0
		PGA (2)	—	2.0	—	—	—
EPF10K100A	240	RQFP	1.0	13.0	11.0	10.0	9.0
	356	BGA	1.0	12.0	11.0	10.0	9.0
	484	FBGA	5.0	22.0	21.0	20.0	18.0
	600	BGA	0.5	10.0	9.0	8.0	7.0
EPF10K100E	208	PQFP	5.0	28.0	26.0	23.0	18.0
	240	PQFP	4.0	23.0	21.0	19.0	16.0
	256	FBGA	6.0	28.0	26.0	25.0	23.0
	356	BGA	1.0	12.0	11.0	10.0	9.0
	484	FBGA	5.0	24.0	23.0	22.0	21.0
EPF10K130V	599	PGA	1.0	8.0	7.0	6.0	4.0
	600	BGA	0.5	10.0	9.0	8.0	7.0
EPF10K130E	240	PQFP	4.0	21.0	19.0	17.0	15.0
	356	BGA	1.0	12.0	11.0	10.0	9.0
	484	FBGA	5.0	23.0	22.0	21.0	20.0
	600	BGA	0.5	10.0	9.0	8.0	7.0
	672	FBGA	5.0	21.0	20.0	19.0	18.0

Table 30. Thermal Resistance of FLEX 10K Devices (Continued)

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EPF10K200E	599	PGA	1.0	8.0	7.0	6.0	4.0
	600	BGA	0.5	10.0	9.0	8.0	7.0
	672	FBGA	5.0	20.0	19.0	18.0	17.0
EPF10K200S	240	RQFP	1.0	13.0	11.0	10.0	9.0
	356	BGA	1.0	12.0	11.0	10.0	9.0
	484	FBGA	5.0	22.0	21.0	20.0	19.0
	600	BGA	0.5	10.0	9.0	8.0	7.0
	672	FBGA	5.0	21.0	20.0	19.0	18.0
EPF10K250A	599	PGA	1.0	8.0	7.0	6.0	4.0
	600	BGA	0.5	10.0	9.0	8.0	7.0

Notes to Table 30:

- (1) With attached pin-fin heat sink.
 (2) With attached motor-driven fan heat sink.

Table 31. Thermal Resistance of FLEX 8000 Devices

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EPF8282A	84	PLCC	10.0	30.0	28.0	26.0	23.0
	100	TQFP	11.0	36.0	34.0	32.0	29.0
EPF8452A	84	PLCC	10.0	30.0	28.0	26.0	23.0
	100	TQFP	11.0	35.0	33.0	31.0	28.0
	160	PQFP	6.0	32.0	31.0	30.0	28.0
	160	PGA	6.0	20.0	13.0	10.0	8.0
EPF8636A	84	PLCC	10.0	29.0	28.0	26.0	23.0
	160	PQFP	6.0	32.0	31.0	30.0	27.0
	192	PGA	6.0	16.0	11.0	8.0	6.0
	208	PQFP	5.0	30.0	38.0	26.0	20.0
	208	RQFP	1.0	17.0	16.0	15.0	14.0

Table 31. Thermal Resistance of FLEX 8000 Devices (Continued)

EPF8820A	144	TQFP	9.0	26.0	25.0	24.0	23.0
	160	PQFP	6.0	32.0	31.0	30.0	27.0
	192	PGA	6.0	16.0	11.0	8.0	6.0
	208	PQFP	5.0	29.0	27.0	25.0	20.0
	208	RQFP	1.0	17.0	16.0	15.0	14.0
	225	BGA	6.0	28.0	19.0	14.0	11.0
EPF81188A	208	PQFP	5.0	28.0	26.0	24.0	19.0
	232	PGA	2.0	14.0	10.0	7.0	5.0
	240	PQFP	4.0	24.0	21.0	19.0	16.0
	240	RQFP	1.0	14.0	12.0	11.0	10.0
EPF81500A	240	PQFP	4.0	22.0	20.0	19.0	16.0
	240	RQFP	1.0	13.0	12.0	11.0	10.0
	280	PGA	2.0	14.0	10.0	7.0	5.0
	304	RQFP	1.0	11.0	10.0	9.0	8.0

Table 32. Thermal Resistance of FLEX 6000 Devices

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EPF6010A	100	TQFP	11.0	35.0	33.0	31.0	28.0
	144	TQFP	10.0	28.0	26.0	25.0	24.0
EPF6016	144	TQFP	10.0	28.0	26.0	25.0	24.0
	208	PQFP	5.0	30.0	28.0	26.0	21.0
	240	PQFP	4.0	26.0	24.0	21.0	17.0
	256	BGA	6.0	28.0	22.0	20.0	19.0
EPF6016A	100	TQFP	11.0	35.0	33.0	31.0	28.0
		FBGA	14.0	36.0	34.0	32.0	29.0
	144	TQFP	10.0	29.0	28.0	26.0	24.0
	208	PQFP	5.0	30.0	29.0	26.0	21.0
	256	FBGA	10.0	32.0	30.0	29.0	26.0
EPF6024A	144	TQFP	10.0	27.0	26.0	25.0	24.0
	208	PQFP	5.0	29.0	28.0	26.0	20.0
	240	PQFP	4.0	26.0	23.0	21.0	17.0
	256	BGA	6.0	28.0	22.0	20.0	19.0
		FBGA	8.0	30.0	29.0	27.0	25.0

Table 33. Thermal Resistance of Excalibur Embedded Processor Solutions

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W) Still Air	θ_{JA} (° C/W) 100 ft./min.	θ_{JA} (° C/W) 200 ft./min.	θ_{JA} (° C/W) 400 ft./min.
EPXA1	484	FBGA	4.0	20.0	18.3	15.8	13.9
	672	Flip Chip FBGA (Cu lid)	0.52	11.3	9.3	7.9	6.7
	672	Flip Chip FBGA (AlSiC lid)	0.78	12.2	10.2	8.6	7.2
EPXA4	672	Flip Chip FBGA (Cu lid)	0.21	10.8	8.8	7.3	6.2
	672	Flip Chip FBGA (AlSiC lid)	0.31	11.6	9.6	7.9	6.6
	1,020	Flip Chip FBGA (Cu lid)	0.21	9.9	7.9	6.5	5.4
	1,020	Flip Chip FBGA (AlSiC lid)	0.32	10.4	8.5	6.9	5.7
EPXA10	1,020	Flip Chip FBGA (Cu lid)	0.11	9.6	7.6	6.2	5.1
	1,020	Flip Chip FBGA (AlSiC lid)	0.17	10.0	8.0	6.4	5.7

Table 34. Thermal Resistance of Classic Devices

Device	Pin Count	Package	θ_{JC} (° C/W)	θ_{JA} (° C/W)
EP600I	24	PDIP	22.0	67.0
		CerDIP	18.0	60.0
	28	PLCC	16.0	64.0
EP610	24	CerDIP	10.0	60.0
		PDIP	18.0	55.0
		SOIC	17.0	77.0
	28	PLCC	13.0	74.0
EP610I	24	CerDIP	18.0	60.0
		PDIP	22.0	67.0
	28	PLCC	16.0	64.0
EP900I	40	PDIP	23.0	49.0
	44	PLCC	10.0	58.0
EP910	40	CerDIP	12.0	40.0
		PDIP	23.0	49.0
	44	PLCC	10.0	58.0
EP910I	40	CerDIP	17.0	44.0
		PDIP	29.0	51.0
	44	PLCC	16.0	55.0
EP1800I	68	PLCC	13.0	44.0
EP1810	68	JLCC	12.0	47.0
		PLCC	13.0	44.0
		PGA	6.0	38.0

Package Outlines


The package outlines on the following pages are listed in order of ascending pin count. Altera package outlines meet the requirements of JEDEC Publication No. 95.

8-Pin Plastic Dual In-Line Package (PDIP)

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in inches.
- Pin 1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	P
Package Acronym	PDIP
Leadframe Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.) Pb-free: Matte Sn
JEDEC Outline Reference	MS-001 Variation: BA
Maximum Lead Coplanarity	NA
Weight	0.5 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Inches		
	Min.	Nom.	Max.
A	–	–	0.170
A1	0.015	–	–
A2	0.130 TYP		
D	0.360	–	0.380
E	0.300	0.310	0.325
E1	0.240	0.250	0.260
L	0.125	–	0.135
b	0.016	0.018	0.020
c	0.008	0.010	0.014
e	0.100 BSC		

Package Outline



8-Pin Small Outline Integrated Circuit Package (SOIC)

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin 1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.


Package Information	
Description	Specification
Ordering Code Reference	S
Package Acronym	SOIC
Leadframe Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ) Pb-free: NiPdAu (Preplated)
JEDEC Outline Reference	MS-012 Var. AA
Maximum Lead Coplanarity	0.1 mm
Weight	0.08 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Minimum	Nom.	Maximum
A	1.35	—	1.75
A1	0.10	—	0.25
A2	1.25	—	1.65
D	4.90 BSC		
E	6.00 BSC		
E1	3.90 BSC		
L	0.40	—	1.27
L1	1.04 REF		
B	0.31	—	0.51
c	0.17	—	0.25
e	1.27 BSC		
θ	0°	—	8°

Package Outline



See Detail A




16-Pin Small Outline Integrated Circuit Package (SOIC)

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin 1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	S
Package Acronym	SOIC
Leadframe Material	Copper
Lead Finish (Plating)	Pb-free: NiPdAu (Preplated)
JEDEC Outline Reference	MS-013 Var. AA
Maximum Lead Coplanarity	0.1 mm
Weight	0.4 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Minimum	Nom.	Maximum
A	2.35	—	2.65
A1	0.10	—	0.30
A2	2.05	—	2.55
D	10.30 BSC		
E	10.30 BSC		
E1	7.50 BSC		
L	0.40	—	1.27
L1	1.40 REF		
b	0.31	—	0.51
c	0.20	—	0.33
e	1.27 BSC		
θ	0°	—	8°

Package Outline




20-Pin Plastic J-Lead Chip Carrier (PLCC)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in inches.
- Pin 1 is generally indicated by an indentation in the plastic body, in Pin 1's proximity, on package surface.

Package Information	
Description	Specification
Ordering Code Reference	L
Package Acronym	PLCC
Leadframe Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.) Pb-free: Matte Sn
JEDEC Outline Reference	MS-018 Variation: AA
Maximum Lead Coplanarity	0.004 inches (0.10mm)
Weight	0.8 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Inches		
	Min.	Nom.	Max.
A	0.165	0.172	0.180
A1	0.020	–	–
A2	0.150 TYP		
D	0.385	0.390	0.395
D1	0.350	0.353	0.356
D2	0.290	0.310	0.330
E	0.385	0.390	0.395
E1	0.350	0.353	0.356
E2	0.290	0.310	0.330
b	0.013	–	0.021
c	0.010 TYP		
e	0.050 TYP		

Package Outline




24-Pin Ceramic Dual In-Line Package (CerDIP)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in inches.
- Pin 1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

<i>Package Information</i>	
Description	Specification
Ordering Code Reference	D
Package Acronym	CerDIP
Leadframe Material	Alloy 42
Lead Finish	Regular: 63Sn:37Pb (Typ.)
JEDEC Outline Reference	MS-030 Variation: AF
Maximum Lead Coplanarity	NA
Weight	4.1 g
Moisture Sensitivity Level	Printed on moisture barrier bag

<i>Package Outline Dimension Table</i>			
Symbol	Inches		
	Min.	Nom.	Max.
A	–	–	0.200
A1	0.015	0.028	0.041
D	1.240	1.260	1.280
E	0.290	0.305	0.320
E1	0.280	0.295	0.310
L	0.125	–	–
b	0.015	0.018	0.021
e	0.100 BSC		

Package Outline




24-Pin Plastic Dual In-Line Package (PDIP)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in inches.
- Pin 1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	P
Package Acronym	PDIP
Leadframe Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.) Pb-free: Matte Sn
JEDEC Outline Reference	MS-001 Variation: AF
Maximum Lead Coplanarity	NA
Weight	1.7 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Inches		
	Min.	Nom.	Max.
A	–	–	0.170
A1	0.015	–	–
A2	0.130 TYP		
D	1.245	1.250	1.255
E	0.300	0.310	0.325
E1	0.245	–	0.270
L	0.125	–	0.135
b	0.014	0.018	0.022
c	0.008	0.010	0.014
e	0.100 BSC		

Package Outline




24-Pin Small Outline Integrated Circuit Package (SOIC)

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin 1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	S
Package Acronym	SOIC
Leadframe Material	Copper
Lead Finish (Plating)	Regular 85Sn:15Pb (Typ)
JEDEC Outline Reference	MS-013 Variation: AD
Maximum Lead Coplanarity	0.1 mm
Weight	0.6 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Minimum	Nom.	Maximum
A	2.35	—	2.65
A1	0.10	—	0.30
A2	2.05	—	2.55
D	15.40 BSC		
E	10.30 BSC		
E1	7.50 BSC		
L	0.40	—	1.27
L1	1.40 REF		
b	0.31	—	0.51
c	0.20	—	0.33
e	1.27 BSC		
θ	0°	—	8°

Package Outline




28-Pin Plastic J-Lead Chip Carrier (PLCC)

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in inches.
- Pin 1 is generally indicated by an indentation in the plastic body, in Pin 1's proximity, on package surface.

Package Information	
Description	Specification
Ordering Code Reference	L
Package Acronym	PLCC
Leadframe Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.) Pb-free: Matte Sn
JEDEC Outline Reference	MS-018 Variation: AB
Maximum Lead Coplanarity	0.004 inches (0.10 mm)
Weight	1.1 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Inches		
	Min.	Nom.	Max.
A	0.165	0.172	0.180
A1	0.020	—	—
A2	0.150 TYP		
D	0.485	0.490	0.495
D1	0.450	0.453	0.456
D2	0.382	0.410	0.438
E	0.485	0.490	0.495
E1	0.450	0.453	0.456
E2	0.382	0.410	0.438
b	0.013	—	0.021
c	0.010 TYP		
e	0.050 TYP		

Package Outline




32-Pin Plastic Thin Quad Flat Pack (TQFP)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin 1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	T
Package Acronym	TQFP
Leadframe Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.) Pb-free: Matte Sn
JEDEC Outline Reference	MS-026 Variation: ABA
Maximum Lead Coplanarity	0.004 inches (0.1mm)
Weight	0.2 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	1.20
A1	0.05	–	0.15
A2	0.95	1.00	1.05
D	9.00 BSC		
D1	7.00 BSC		
E	9.00 BSC		
E1	7.00 BSC		
L	0.45	0.60	0.75
L1	1.00 REF		
S	0.20	–	–
b	0.30	0.37	0.45
c	0.09	–	0.20
e	0.80 BSC		
θ	0°	3.5°	7°

Package Outline




40-Pin Ceramic Dual In-Line Package (CerDIP)

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in inches.
- Pin 1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	D
Package Acronym	CerDIP
Leadframe Material	Alloy 42
Lead Finish	Regular: 63Sn:37Pb (Typ.)
JEDEC Outline Reference	MS-032 Variation: AD
Maximum Lead Coplanarity	N/A
Weight	12.8 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Inches		
	Min.	Nom.	Max.
A	–	–	0.225
A1	0.015	0.025	0.035
D	2.030	2.050	2.070
E	0.600	0.610	0.620
E1	0.510	0.550	0.590
L	0.125	–	–
b	0.016	0.018	0.020
c	0.008	0.010	0.012
e	0.100 BSC		

Package Outline




40-Pin Plastic Dual In-Line Package (PDIP)

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in inches.
- Pin 1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	P
Package Acronym	PDIP
Leadframe Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.)
JEDEC Outline Reference	MS-011 Variation: AC
Maximum Lead Coplanarity	N/A
Weight	6.0 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Inches		
	Min.	Nom.	Max.
A	–	–	0.190
A1	0.015	–	–
A2	0.150 BSC		
D	2.030	2.050	2.070
E	0.600	–	0.625
E1	0.520	0.540	0.560
L	0.125	–	0.135
b	0.015	0.018	0.022
c	0.008	–	0.012
e	0.100 BSC		

Package Outline




44-Pin Plastic J-Lead Chip Carrier (PLCC)

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in inches.
- Pin 1 is generally indicated by an indentation in the plastic body, in Pin 1's proximity, on package surface.

Package Information	
Description	Specification
Ordering Code Reference	L
Package Acronym	PLCC
Leadframe Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.) Pb-free: Matte Sn
JEDEC Outline Reference	MS-018 Variation: AC
Maximum Lead Coplanarity	0.004 inches (0.10 mm)
Weight	2.3 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Inches		
	Min.	Nom.	Max.
A	0.165	0.172	0.180
A1	0.020	–	–
A2	0.150 TYP		
D	0.685	0.690	0.695
D1	0.650	0.653	0.656
D2	0.582	0.610	0.638
E	0.685	0.690	0.695
E1	0.650	0.653	0.656
E2	0.582	0.610	0.638
b	0.013	–	0.021
c	0.010 TYP		
e	0.050 TYP		

Package Outline



44-Pin Plastic Quad Flat Pack (PQFP)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin 1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	Q
Package Acronym	PQFP
Leadframe Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.) Pb-free: Matte Sn
JEDEC Outline Reference	MS-022 Variation: AB
Maximum Lead Coplanarity	0.004 inches (0.10 mm)
Weight	0.5 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	2.45
A1	–	–	0.25
A2	1.80	2.00	2.20
D	13.20 BSC		
D1	10.00 BSC		
E	13.20 BSC		
E1	10.00 BSC		
L	0.73	0.88	1.03
L1	1.60 REF		
S	0.20	–	–
b	0.29	–	0.45
c	0.11	–	0.23
e	0.80 BSC		
θ	0°	–	7°


44-Pin Plastic Thin Quad Flat Pack (TQFP)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin 1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	T
Package Acronym	TQFP
Leadframe Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.) Pb-free: Matte Sn
JEDEC Outline Reference	MS-026 Variation: ACB
Maximum Lead Coplanarity	0.004 inches (0.1mm)
Weight	0.3 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	1.20
A1	0.05	–	0.15
A2	0.95	–	–
D	12.00 BSC		
D1	10.00 BSC		
E	12.00 BSC		
E1	10.00 BSC		
L	0.45	0.60	0.75
L1	1.00 REF		
S	0.20	–	–
b	0.30	0.37	0.45
c	0.09	–	0.20
e	0.80 BSC		
θ	0°	3.5°	7°

Package Outline




49-Pin Ultra FineLine BGA® (UBGA)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	U
Package Acronym	UBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MO-216 Variation: BAB-2
Maximum Lead Coplanarity	0.005 inches (0.12mm)
Weight	0.1 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	1.55
A1	0.20	–	–
A2	–	–	1.35
A3	0.70 TYP		
D	7.00 BSC		
E	7.00 BSC		
b	0.40	0.50	0.60
e	0.80 BSC		

Package Outline




68-Pin Ceramic Pin-Grid Array (PGA)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in inches.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	G
Package Acronym	PGA
Leadframe Material	Alloy 42
Lead Finish	Gold Over Nickel Plate
JEDEC Outline Reference	MO-066 Variation: AC
Maximum Lead Coplanarity	N/A
Weight	10.4 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Inches		
	Min.	Nom.	Max.
A	0.154	0.177	0.200
A1	0.050 TYP		
A2	0.114	0.127	0.140
D	1.100	1.120	1.140
E	1.100	1.120	1.140
L	0.130 TYP		
b	0.016	0.018	0.020
e	0.100 BSC		

Package Outline



68-Pin Plastic J-Lead Chip Carrier (PLCC)

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in inches.
- Pin 1 is generally indicated by an indentation in the plastic body, in Pin 1's proximity, on package surface.

Package Information	
Description	Specification
Ordering Code Reference	L
Package Acronym	PLCC
Lead Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.) Pb-free: Matte Sn
JEDEC Outline Reference	MS-018 Variation: AE
Maximum Lead Coplanarity	0.004 inches (0.10 mm)
Weight	4.6 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Inches		
	Min.	Nom.	Max.
A	0.165	0.172	0.180
A1	0.020	—	—
A2	0.150 TYP		
D	0.985	0.990	0.995
D1	0.950	0.954	0.958
D2	0.882	0.910	0.938
E	0.985	0.990	0.995
E1	0.950	0.954	0.958
E2	0.882	0.910	0.938
b	0.013	—	0.021
c	0.008 TYP		
e	0.050 TYP		

Package Outline



84-Pin Plastic J-Lead Chip Carrier (PLCC)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in inches.
- Pin 1 is generally indicated by an indentation in the plastic body, in Pin 1's proximity, on package surface.

Package Information	
Description	Specification
Ordering Code Reference	L
Package Acronym	PLCC
Leadframe Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.) Pb-free: Matte Sn
JEDEC Outline Reference	MS-018 Variation: AF
Maximum Lead Coplanarity	0.004 inches (0.10mm)
Weight	6.8 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Inches		
	Min.	Nom.	Max.
A	0.165	0.172	0.180
A1	0.020	–	–
A2	0.150 TYP		
D	1.185	1.190	1.195
D1	1.150	1.154	1.158
D2	1.082	1.110	1.138
E	1.185	1.190	1.195
E1	1.150	1.154	1.158
E2	1.082	1.110	1.138
b	0.013	–	0.021
c	0.008 TYP		
e	0.050 TYP		


88-Pin Ultra FineLine BGA® (UBGA)

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	U
Package Acronym	UBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline	MO-219
Maximum Lead Coplanarity	0.005 inches (0.12 mm)
Weight	0.2 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	—	—	1.40
A1	0.25	—	—
A2	0.80	—	—
D	11.00 BSC		
E	8.00 BSC		
b	0.40	0.45	0.50
e	0.80 BSC		

Package Outline



100-Pin FineLine BGA® (FBGA) - Option 1


- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on the package surface.

Note: This POD is applicable to F100 packages of all products except MAX II, which is assembled in Option 2 package outlines.

Package Information	
Description	Specification
Ordering Code Reference	F
Package Acronym	FBGA
Substrate Material	BT
Solder ball composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MO-192 Variation: AAC-1
Maximum Lead Coplanarity	0.008 inches (0.20mm)
Weight	1.6 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	1.70
A1	0.30	–	–
A2	0.25	–	1.10
A3	–	–	0.80
D	11.00 BSC		
E	11.00 BSC		
b	0.50	0.60	0.70
e	1.00 BSC		

Package Outline



100-Pin FineLine BGA® (FBGA) - Option 2


- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Note: This POD is applicable to F100 packages of the MAX II device only.

Package Information	
Description	Specification
Ordering Code Reference	F
Package Acronym	FBGA
Substrate Material	BT
Solder ball composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MO-192 Variation: DAC-1
Maximum Lead Coplanarity	0.008 inches (0.20mm)
Weight	1.6 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	1.55
A1	0.25	–	–
A2	1.05 Ref		
A3	–	–	0.80
D	11.00 BSC		
E	11.00 BSC		
b	0.45	0.50	0.55
e	1.00 BSC		

Package Outline



100-Pin Plastic Quad Flat Pack (PQFP) - Option 1


- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin 1 may be indicated by an ID dot, or a special feature, in its proximity on the package surface.

Note: This POD is applicable to Q100 packages of all products not noted in Option 2.

Package Information	
Description	Specification
Ordering Code Reference	Q
Package Acronym	PQFP
Leadframe Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.) Pb-free: Matte Sn
JEDEC Outline Reference	MS-022 Variation: GC-1
Maximum Lead Coplanarity	0.004 inches (0.10mm)
Weight	1.6 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	3.40
A1	0.25	–	0.50
A2	2.50	2.70	2.90
D	17.20 BSC		
D1	14.00 BSC		
E	23.20 BSC		
E1	20.00 BSC		
L	0.73	0.88	1.03
L1	1.60 REF		
S	0.20	–	–
b	0.22	–	0.40
c	0.11	–	0.23
e	0.65 BSC		
θ	0°	–	7°

Package Outline



100-Pin Plastic Quad Flat Pack (PQFP) - Option 2


- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin 1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Note: This POD is only applicable to Q100 packages of EPC8 & EPC16 manufactured in Japan. Refer to PCN0506 for details.

Package Information	
Description	Specification
Ordering Code Reference	Q
Package Acronym	PQFP
Leadframe Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.)
JEDEC Outline Reference	N/A
Maximum Lead Coplanarity	0.006 inches (0.15mm)
Weight	1.6 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	1.75	1.95	2.15
A1	0.0	0.10	0.20
A2	1.85 TYP		
D	17.90	18.30	18.70
D1	13.80	14.00	14.20
E	23.90	24.30	24.70
E1	19.80	20.00	20.20
L	1.20 REF		
L1	2.15 REF		
b	0.20	0.30	0.40
c	0.10	0.15	0.20
e	0.65 BSC		
θ	0°	–	10°

Package Outline





100-Pin Plastic Thin Quad Flat Pack (TQFP)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin 1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	T
Package Acronym	TQFP
Leadframe Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.) Pb-free: Matte Sn
JEDEC Outline Reference	MS-026 Variation: AED
Maximum Lead Coplanarity	0.003 inches (0.08mm)
Weight	0.5 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	1.20
A1	0.05	–	0.15
A2	0.95	1.00	1.05
D	16.00 BSC		
D1	14.00 BSC		
E	16.00 BSC		
E1	14.00 BSC		
L	0.45	0.60	0.75
L1	1.00 REF		
S	0.20	–	–
b	0.17	0.22	0.27
c	0.09	–	0.20
e	0.50 BSC		
θ	0°	3.5°	7°

Package Outline




100-Pin Micro FineLine BGA® (MBGA)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	M
Package Acronym	MBGA
Substrate Material	BT
Solder ball composition	Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MO-195 Variation: AC
Maximum Lead Coplanarity	0.005 inches (0.12mm)
Weight	0.1 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	1.20
A1	0.15	–	–
A2	–	–	1.00
A3	0.60 REF		
D	6.00 BSC		
E	6.00 BSC		
b	0.25	0.30	0.35
e	0.50 BSC		

Package Outline




144-Pin FineLine BGA® (FBGA)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	F
Package Acronym	FBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MO-192 Variation: AAD-1
Maximum Lead Coplanarity	0.008 inches (0.20mm)
Weight	1.7 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	1.70
A1	0.30	–	–
A2	0.25	–	1.10
A3	–	–	0.80
D	13.00 BSC		
E	13.00 BSC		
b	0.50	0.60	0.70
e	1.00 BSC		

Package Outline




144-Pin Plastic Thin Quad Flat Pack (TQFP)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin 1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	T
Package Acronym	TQFP
Leadframe Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.) Pb-free: Matte Sn
JEDEC Outline Reference	MS-026 Variation: BFB
Maximum Lead Coplanarity	0.003 inches (0.08mm)
Weight	1.3 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Figure Reference			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	1.60
A1	0.05	–	0.15
A2	1.35	1.40	1.45
D	22.00 BSC		
D1	20.00 BSC		
E	22.00 BSC		
E1	20.00 BSC		
L	0.45	0.60	0.75
L1	1.00 REF		
S	0.20	–	–
b	0.17	0.22	0.27
c	0.09	–	0.20
e	0.50 BSC		
θ	0°	3.5°	7°

Package Outline



160-Pin Ceramic Pin-Grid Array (PGA)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in inches.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	G
Package Acronym	PGA
Leadframe Material	Alloy 42
Lead Finish	Gold Over Nickel Plate
JEDEC Outline Reference	MO-067 Variation: AG
Maximum Lead Coplanarity	N/A
Weight	19.9 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Inches		
	Min.	Nom.	Max.
A	0.160	0.190	0.220
A1	0.050 TYP		
A2	0.120	0.140	0.160
D	1.540	1.560	1.580
E	1.540	1.560	1.580
L	0.130 TYP		
b	0.016	0.018	0.020
e	0.100 BSC		


160-Pin Plastic Quad Flat Pack (PQFP)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin 1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	Q
Package Acronym	PQFP
Leadframe Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.) Pb-free: Matte Sn
JEDEC Outline Reference	MS-022 Variation: DD-1
Maximum Lead Coplanarity	0.004 inches (0.10mm)
Weight	5.4 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	4.10
A1	0.25	–	0.50
A2	3.20	3.40	3.60
D	31.20 BSC		
D1	28.00 BSC		
E	31.20 BSC		
E1	28.00 BSC		
L	0.50	–	1.03
L1	1.60 REF		
S	0.20	–	–
b	0.22	–	0.40
c	0.09	–	0.23
e	0.65 BSC		
θ	0°	–	7°

Package Outline




169-Pin Ultra FineLine BGA® (UBGA)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	U
Package Acronym	UBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MO-216 Variation: BAF-1
Maximum Lead Coplanarity	0.005 inches (0.12mm)
Weight	0.4 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	1.70
A1	0.20	–	–
A2	0.65	–	–
A3	0.70 TYP		
D	11.00 BSC		
E	11.00 BSC		
b	0.40	0.50	0.60
e	0.80 BSC		

Package Outline




192-Pin Ceramic Pin-Grid Array (PGA)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in inches.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	G
Package Acronym	PGA
Leadframe Material	Alloy 42
Lead Finish	Gold Over Nickel Plate
JEDEC Outline Reference	MO-067 Variation: AJ
Maximum Lead Coplanarity	N/A
Weight	21.0 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Inches		
	Min.	Nom.	Max.
A	0.167	0.192	0.217
A1	0.050 TYP		
A2	0.127	0.142	0.157
D	1.740	1.760	1.780
E	1.740	1.760	1.780
L	0.130 TYP		
b	0.016	0.018	0.020
e	0.100 BSC		

Package Outline




208-Pin Plastic Quad Flat Pack (PQFP)

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin 1 may be indicated by an ID dot in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	Q
Package Acronym	PQFP
Lead Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.) Pb-free: Matte Sn
JEDEC Outline Reference	MS-029 Variation: FA-1
Maximum Lead Coplanarity	0.003 inches (0.08 mm)
Weight	5.7 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	—	—	4.10
A1	0.25	—	0.50
A2	3.20	3.40	3.60
D	30.60 BSC		
D1	28.00 BSC		
E	30.60 BSC		
E1	28.00 BSC		
L	0.50	0.60	0.75
L1	1.30 REF		
S	0.20	—	—
b	0.17	—	0.27
c	0.09	—	0.20
e	0.50 BSC		
θ	0°	3.5°	8°

Package Outline




208-Pin Power Quad Flat Pack (RQFP)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin 1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	R
Package Acronym	RQFP
Leadframe Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.) Pb-free: Matte Sn
JEDEC Outline Reference	MS-029 Variation: FA-1
Maximum Lead Coplanarity	0.003 inches (0.08mm)
Weight	10.8 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	4.10
A1	0.25	–	0.50
A2	3.20	3.40	3.60
D	30.60 BSC		
D1	28.00 BSC		
E	30.60 BSC		
E1	28.00 BSC		
L	0.45	0.60	0.75
L1	1.30 REF		
S	0.20	–	–
b	0.17	–	0.27
c	0.09	–	0.20
e	0.50 BSC		
θ	0°	3.5°	8°

Package Outline




232-Pin Ceramic Pin-Grid Array (PGA)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in inches.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	G
Package Acronym	PGA
Leadframe Material	Alloy 42
Lead Finish	Gold Over Nickel Plate
JEDEC Outline Reference	MO-067 Variation: AJ
Maximum Lead Coplanarity	N/A
Weight	25.5 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Inches		
	Min.	Nom.	Max.
A	0.174	0.192	0.210
A1	0.050 TYP		
A2	0.134	0.142	0.150
D	1.740	1.760	1.780
E	1.740	1.760	1.780
L	0.130 TYP		
b	0.016	0.018	0.020
e	0.100 BSC		

Package Outline




240-Pin Plastic Quad Flat Pack (PQFP)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin 1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	Q
Package Acronym	PQFP
Leadframe Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.) Pb-free: Matte Sn
JEDEC Outline Reference	MS-029 Variation: GA
Maximum Lead Coplanarity	0.003 inches (0.08mm)
Weight	7.0 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	4.10
A1	0.25	–	0.50
A2	3.20	3.40	3.60
D	34.60 BSC		
D1	32.00 BSC		
E	34.60 BSC		
E1	32.00 BSC		
L	0.45	0.60	0.75
L1	1.30 REF		
S	0.20	–	–
b	0.17	–	0.27
c	0.09	–	0.20
e	0.50 BSC		
θ	0°	3.5°	8°

Package Outline




240-Pin Power Quad Flat Pack (RQFP)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin 1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	R
Package Acronym	RQFP
Leadframe Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.) Pb-free: Matte Sn
JEDEC Outline Reference	MS-029 Variation: GA
Maximum Lead Coplanarity	0.003 inches (0.08mm)
Weight	15.1 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	4.10
A1	0.25	–	0.50
A2	3.20	3.40	3.60
D	34.60 BSC		
D1	32.00 BSC		
E	34.60 BSC		
E1	32.00 BSC		
L	0.45	0.60	0.75
L1	1.30 REF		
S	0.20	–	–
b	0.17	–	0.27
c	0.09	–	0.20
e	0.50 BSC		
θ	0°	3.5°	8°

Package Outline



256-Pin FineLine BGA® (FBGA) - Option 1


- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Note: This POD is applicable to F256 packages of all products except Cyclone II, which is assembled in Option 2 package outlines.

Package Information	
Description	Specification
Ordering Code Reference	F
Package Acronym	FBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: AAF-1
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	1.9 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
	Millimeters		
	Min.	Nom.	Max.
A	–	–	2.20
A1	0.30	–	–
A2	–	–	1.80
A3	0.70 REF		
D	17.00 BSC		
E	17.00 BSC		
b	0.50	0.60	0.70
e	1.00 BSC		

Package Outline



256-Pin FineLine BGA® (FBGA) - Option 2


- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on the package surface.

Note: This POD is applicable to F256 packages of the Cyclone II product only.

Package Information	
Description	Specification
Ordering Code Reference	F
Package Acronym	FBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MO-192 Variation: DAF-1
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	1.9 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
	Millimeters		
	Min.	Nom.	Max.
A	–	–	1.55
A1	0.25	–	–
A2	1.05 REF		
A3	–	–	0.80
D	17.00 BSC		
E	17.00 BSC		
b	0.45	0.50	0.55
e	1.00 BSC		

Package Outline




256-Pin Ball-Grid Array (BGA) - Option 1

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	B
Package Acronym	BGA
Substrate Material	Tin-lead alloy (63/37)
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MO-192 Variation: BAL-2
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	4.3 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	1.70
A1	0.35	–	–
A2	0.25	–	1.10
D	27.00 BSC		
E	27.00 BSC		
b	0.60	0.75	0.90
e	1.27 BSC		

Package Outline




256-Pin Plastic Ball-Grid Array (BGA) - Option 2

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	B
Package Acronym	BGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: BAL-2
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	2.1 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	2.60
A1	0.35	–	–
A2	–	–	2.20
A3	–	–	1.80
D	27.00 BSC		
E	27.00 BSC		
b	0.60	0.75	0.90
e	1.27 BSC		

Package Outline




256-Pin Micro FineLine BGA® (MBGA)

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

<i>Package Information</i>	
Description	Specification
Ordering Code Reference	M
Package Acronym	MBGA
Substrate Material	BT
Solder Ball Composition	Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MO-195 Variation: BH
Maximum Lead Coplanarity	0.005 inches (0.12mm)
Weight	0.4 g
Moisture Sensitivity Level	Printed on moisture barrier bag

<i>Package Outline Dimension Table</i>			
	Millimeters		
	Min.	Nom.	Max.
A	–	–	1.20
A1	0.15	–	–
A2	–	–	1.00
A3	0.60 REF		
D	11.00 BSC		
E	11.00 BSC		
b	0.25	0.30	0.35
e	0.50 BSC		

Package Outline




256-Pin Ultra FineLine BGA® (UBGA)

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	U
Package Acronym	UBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MO-216 Variation: BAJ-2
Maximum Lead Coplanarity	0.005 inches (0.12mm)
Weight	1.0 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
	Millimeters		
	Min.	Nom.	Max.
A	–	–	2.20
A1	0.20	–	–
A2	0.65	–	–
A3	0.80 TYP		
D	14.00 BSC		
E	14.00 BSC		
b	0.40	0.50	0.60
e	0.80 BSC		

Package Outline




280-Pin Ceramic Pin-Grid Array (PGA)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in inches.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	G
Package Acronym	PGA
Leadframe Material	Alloy 42
Lead Finish	Gold Over Nickel Plate
JEDEC Outline Reference	MO-067 Variation: AL
Maximum Lead Coplanarity	N/A
Weight	29.5 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Inches		
	Min.	Nom.	Max.
A	0.165	0.185	0.205
A1	0.050 TYP		
A2	0.125	0.135	0.145
D	1.940	1.960	1.980
E	1.940	1.960	1.980
L	0.130 TYP		
b	0.016	0.018	0.020
e	0.100 BSC		

Package Outline




304-Pin Power Quad Flat Pack (RQFP)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin 1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	R
Package Acronym	RQFP
Leadframe Material	Copper
Lead Finish (Plating)	Regular: 85Sn:15Pb (Typ.) Pb-free: Matte Sn
JEDEC Outline Reference	MS-029 Variation: JA
Maximum Lead Coplanarity	0.003 inches (0.08mm)
Weight	26.3 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	4.50
A1	0.25	–	0.50
A2	3.55	3.80	4.05
D	42.60 BSC		
D1	40.00 BSC		
E	42.60 BSC		
E1	40.00 BSC		
L	0.45	0.60	0.75
L1	1.30 REF		
S	0.20	–	–
b	0.17	–	0.27
c	0.09	–	0.20
e	0.50 BSC		
θ	0°	3.5°	8°

Package Outline




324-Pin FineLine BGA® (FBGA)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	F
Package Acronym	FBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: AAG-1
Maximum Lead Coplanarity	0.008 inches (0.20mm)
Weight	2.0 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	2.20
A1	0.30	–	–
A2	–	–	1.80
A3	0.70 REF		
D	19.00 BSC		
E	19.00 BSC		
b	0.50	0.60	0.70
e	1.00 BSC		

Package Outline



356-Pin Ball-Grid Array (BGA)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	B
Package Acronym	BGA
Substrate Material	BT or tape
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MO-192 Variation: BAR-2
Maximum Lead Coplanarity	0.008 inches (0.20mm)
Weight	7.0 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	1.70
A1	0.35	–	–
A2	0.25	–	1.10
D	35.00 BSC		
E	35.00 BSC		
b	0.60	0.75	0.90
e	1.27 BSC		


400-Pin FineLine BGA® (FBGA)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	F
Package Acronym	FBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: AAH-1
Maximum Lead Coplanarity	0.008 inches (0.20mm)
Weight	1.9 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	2.20
A1	0.30	–	–
A2	–	–	1.80
A3	0.80 REF		
D	21.00 BSC		
E	21.00 BSC		
b	0.50	0.60	0.70
e	1.00 BSC		

Package Outline




403-Pin Ceramic Pin-Grid Array (PGA)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in inches.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	G
Package Acronym	PGA
Leadframe Material	Alloy 42
Lead Finish	Gold Over Nickel Plate
JEDEC Outline Reference	MO-128 Variation: AL
Maximum Lead Coplanarity	N/A
Weight	47.7 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Inches		
	Min.	Nom.	Max.
A	0.157	0.180	0.203
A1	0.050 TYP		
A2	0.117	0.130	0.143
D	1.940	1.960	1.980
E	1.940	1.960	1.980
L	0.130 TYP		
b	0.016	0.018	0.020
e	0.100 BSC		

Package Outline




484-Pin FineLine BGA® (FBGA) - Flip Chip -Option 1

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on the package surface.

Package Information	
Description	Specification
Ordering Code Reference	F
Package Acronym	FBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: AAJ-1
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	5.8 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	3.50
A1	0.30	–	–
A2	0.25	–	3.00
A3	–	–	2.50
D	23.00 BSC		
E	23.00 BSC		
b	0.50	0.60	0.70
e	1.00 BSC		

Package Outline




484-Pin FineLine BGA® (FBGA) - Option 2

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	F
Package Acronym	FBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: AAJ-1
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	2.4 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	2.60
A1	0.30	–	–
A2	–	–	2.20
A3	–	–	1.80
D	23.00 BSC		
E	23.00 BSC		
b	0.50	0.60	0.70
e	1.00 BSC		

Package Outline




484-Pin FineLine BGA® (FBGA) - Option 3

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	F
Package Acronym	FBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: AAJ-1
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	2.3 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	2.60
A1	0.30	–	–
A2	–	–	2.20
A3	–	–	1.80
D	23.00 BSC		
E	23.00 BSC		
b	0.50	0.60	0.70
e	1.00 BSC		

Package Outline




484-Pin Hybrid FineLine BGA® (HBGA) - Flip Chip

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	H
Package Acronym	HBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: AAL-1
Maximum Lead Coplanarity	0.008 inches (0.20mm)
Weight	7.7 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	3.50
A1	0.30	–	–
A2	0.25	–	3.00
A3	–	–	2.50
D	27.00 BSC		
E	27.00 BSC		
b	0.50	0.60	0.70
e	1.00 BSC		

Package Outline




484-Pin Ultra FineLine BGA® (UBGA)

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	U
Package Acronym	UBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MO-216 Variation: BAP-2
Maximum Lead Coplanarity	0.005 inches (0.12mm)
Weight	1.8 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	—	—	2.20
A1	0.20	—	—
A2	0.65	—	—
A3	0.80 TYP		
D	19.00 BSC		
E	19.00 BSC		
b	0.40	0.50	0.60
e	0.80 BSC		

Package Outline




503-Pin Ceramic Pin-Grid Array (PGA)

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in inches.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	G
Package Acronym	PGA
Leadframe Material	Alloy 42
Lead Finish	Gold Over Nickel Plate
JEDEC Outline Reference	MO-128 Variation: AN
Maximum Lead Coplanarity	N/A
Weight	59.0 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
	Inches		
	Min.	Nom.	Max.
A	–	–	0.205
A1	0.050 TYP		
A2	–	–	0.145
D	2.245	2.260	2.275
E	2.245	2.260	2.275
L	0.130 TYP		
b	0.016	0.018	0.020
e	0.100 BSC		

Package Outline




599-Pin Ceramic Pin-Grid Array (PGA)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in inches.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	G
Package Acronym	PGA
Leadframe Material	Alloy 42
Lead Finish	Gold Over Nickel Plate
JEDEC Outline Reference	MO-128 Variation: AP
Maximum Lead Coplanarity	N/A
Weight	69.0 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Inches		
	Min.	Nom.	Max.
A	–	–	0.205
A1	0.050 TYP		
A2	–	–	0.145
D	2.445	2.460	2.475
E	2.445	2.460	2.475
L	0.130 TYP		
b	0.016	0.018	0.020
e	0.100 BSC		

Package Outline




600-Pin Ball-Grid Array (BGA)

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	B
Package Acronym	BGA
Substrate Material	BT or tape
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MO-192 Variation: BAW-1
Maximum Lead Coplanarity	0.008 inches (0.20mm)
Weight	12.0 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	2.00
A1	0.35	–	–
A2	0.25	–	1.10
D	45.00 BSC		
E	45.00 BSC		
b	0.60	0.75	0.90
e	1.27 BSC		

Package Outline




652-Pin Ball-Grid Array (BGA) Flip Chip - Option 1

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	B
Package Acronym	BGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: BAW-1
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	16.1 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	3.50
A1	0.30	–	–
A2	0.25	–	3.00
A3	–	–	2.50
D	45.00 BSC		
E	45.00 BSC		
b	0.60	0.75	0.90
e	1.27 BSC		

Package Outline




652-Pin Plastic Ball-Grid Array (BGA) - Option 2

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	B
Package Acronym	BGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: BAW-1
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	9.6 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	3.20
A1	0.35	–	–
A2	–	–	2.80
A3	–	–	2.40
D	45.00 BSC		
E	45.00 BSC		
b	0.60	0.75	0.90
e	1.27 BSC		

Package Outline




652-Pin Plastic Ball-Grid Array (BGA) - Option 3

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

<i>Package Information</i>	
Description	Specification
Ordering Code Reference	B
Package Acronym	BGA
Substrate Material	BT or tape
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MO-192 Variation: BAW-1
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	14.9 g
Moisture Sensitivity Level	Printed on moisture barrier bag

<i>Package Outline Dimension Table</i>			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	2.00
A1	0.35	–	–
A2	0.25	–	1.10
D	45.00 BSC		
E	45.00 BSC		
b	0.60	0.75	0.90
e	1.27 BSC		

Package Outline



655-Pin Ceramic Pin-Grid Array (PGA)

- All dimensions and tolerances conform to ASME Y14.5M – 1994.
- Controlling dimension is in inches.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	G
Package Acronym	PGA
Leadframe Material	Alloy 42
Lead Finish	Gold Over Nickel Plate
JEDEC Outline Reference	MO-128 Variation: AP
Maximum Lead Coplanarity	N/A
Weight	74.9 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Inches		
	Min.	Nom.	Max.
A	–	–	0.205
A1	0.050 TYP		
A2	–	–	0.145
D	2.445	2.460	2.475
E	2.445	2.460	2.475
L	0.130 TYP		
b	0.016	0.018	0.020
e	0.100 BSC		


672-Pin Platic Ball-Grid Array (BGA)

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

<i>Package Information</i>	
Description	Specification
Ordering Code Reference	B
Package Acronym	BGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: BAR-2
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	5.2 g
Moisture Sensitivity Level	Printed on moisture barrier bag

<i>Package Outline Dimension Table</i>			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	2.60
A1	0.35	–	–
A2	–	–	2.20
A3	–	–	1.80
D	35.00 BSC		
E	35.00 BSC		
b	0.60	0.75	0.90
e	1.27 BSC		

Package Outline




672-Pin FineLine BGA® (FBGA) - Flip Chip - Option 1

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	F
Package Acronym	FBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: AAL-1
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	7.7 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	—	—	3.50
A1	0.30	—	—
A2	0.25	—	3.00
A3	—	—	2.50
D	27.00 BSC		
E	27.00 BSC		
b	0.50	0.60	0.70
e	1.00 BSC		

Package Outline




672-Pin FineLine BGA® (FBGA) - Option 2

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	F
Package Acronym	FBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: AAL-1
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	3.5 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	—	—	2.60
A1	0.30	—	—
A2	—	—	2.20
A3	—	—	1.80
D	27.00 BSC		
E	27.00 BSC		
b	0.50	0.60	0.70
e	1.00 BSC		

Package Outline




672-Pin FineLine BGA® (FBGA) - Option 3

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	F
Package Acronym	FBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: AAL-1
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	3.3 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	—	—	2.60
A1	0.30	—	—
A2	—	—	2.20
A3	—	—	1.80
D	27.00 BSC		
E	27.00 BSC		
b	0.50	0.60	0.70
e	1.00 BSC		

Package Outline



724-Pin Ball-Grid Array (BGA) - Flip Chip


- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	B
Package Acronym	BGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: BAR-1
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	12.4 g
Moisture Sensitivity Level	Printed on moisture barrier bag



Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	3.50
A1	0.30	–	–
A2	0.25	–	3.00
A3	–	–	2.50
D	35.00 BSC		
E	35.00 BSC		
b	0.60	0.75	0.90
e	1.27 BSC		

Package Outline

TOP VIEW



BOTTOM VIEW




780-Pin FineLine BGA® (FBGA) - Flip Chip

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	F
Package Acronym	FBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: AAM-1
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	8.9 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	3.50
A1	0.30	–	–
A2	0.25	–	3.00
A3	–	–	2.50
D	29.00 BSC		
E	29.00 BSC		
b	0.50	0.60	0.70
e	1.00 BSC		

Package Outline




896-Pin FineLine BGA® (FBGA)

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	F
Package Acronym	FBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: AAN-1
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	4.2 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	—	—	2.60
A1	0.30	—	—
A2	—	—	2.20
A3	—	—	1.80
D	31.00 BSC		
E	31.00 BSC		
b	0.50	0.60	0.70
e	1.00 BSC		

Package Outline



956-Pin Ball Grid Array (BGA) - Flip Chip

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	B
Package Acronym	BGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: BAU-1
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	14.6 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	3.50
A1	0.30	–	–
A2	0.25	–	3.00
A3	–	–	2.50
D	40.00 BSC		
E	40.00 BSC		
b	0.60	0.75	0.90
e	1.27 BSC		

Package Outline




1020-Pin FineLine BGA® (FBGA) - Flip Chip

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

Package Information	
Description	Specification
Ordering Code Reference	F
Package Acronym	FBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: AAP-1
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	11.5 g
Moisture Sensitivity Level	Printed on moisture barrier bag

Package Outline Dimension Table			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	3.50
A1	0.30	–	–
A2	0.25	–	3.00
A3	–	–	2.50
D	33.00 BSC		
E	33.00 BSC		
b	0.50	0.60	0.70
e	1.00 BSC		

Package Outline




1508-Pin FineLine BGA® (FBGA) - Flip Chip

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

<i>Package Information</i>	
Description	Specification
Ordering Code Reference	F
Package Acronym	FBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: AAU-1
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	14.6 g
Moisture Sensitivity Level	Printed on moisture barrier bag

<i>Package Outline Dimension Table</i>			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	3.50
A1	0.30	–	–
A2	0.25	–	3.00
A3	–	–	2.50
D	40.00 BSC		
E	40.00 BSC		
b	0.50	0.60	0.70
e	1.00 BSC		

Package Outline




1152-Pin FineLine BGA® (FBGA) - Flip Chip

- All dimensions and tolerances conform to ASME Y14.5M - 1994.
- Controlling dimension is in millimeters.
- Pin A1 may be indicated by an ID dot, or a special feature, in its proximity on package surface.

<i>Package Information</i>	
Description	Specification
Ordering Code Reference	F
Package Acronym	FBGA
Substrate Material	BT
Solder Ball Composition	Regular: 63Sn:37Pb (Typ.) Pb-free: Sn:3Ag:0.5Cu (Typ.)
JEDEC Outline Reference	MS-034 Variation: AAR-1
Maximum Lead Coplanarity	0.008 inches (0.20 mm)
Weight	12.0 g
Moisture Sensitivity Level	Printed on moisture barrier bag

<i>Package Outline Dimension Table</i>			
Symbol	Millimeters		
	Min.	Nom.	Max.
A	–	–	3.50
A1	0.30	–	–
A2	0.25	–	3.00
A3	–	–	2.50
D	35.00 BSC		
E	35.00 BSC		
b	0.50	0.60	0.70
e	1.00 BSC		

Package Outline





101 Innovation Drive
San Jose, CA 95134
(408) 544-7000
<http://www.altera.com>

Copyright © 2006 Altera Corporation. All rights reserved. Altera, The Programmable Solutions Company, the stylized Altera logo, specific device designations, and all other words and logos that are identified as trademarks and/or service marks are, unless noted otherwise, the trademarks and service marks of Altera Corporation in the U.S. and other countries. All other product or service names are the property of their respective holders. Altera products are protected under numerous U.S. and foreign patents and pending applications, maskwork rights, and copyrights. Altera warrants performance of its semiconductor products to current specifications in accordance with Altera's standard warranty, but reserves the right to make changes to any products and services at any time without notice. Altera assumes no responsibility or liability arising out of the application or use of any information, product, or service described herein except as expressly agreed to in writing by Altera Corporation. Altera customers are advised to obtain the latest version of device specifications before relying on any published information and before placing orders for products or services.

