



STM32F10xxx GPIO application examples

Introduction

This application note is intended to provide practical application examples of the STM32F10xxx GPIO peripheral use.

This document, its associated firmware, and other such application notes are written to accompany the STM32F10xxx firmware library. These are available for download from the STMicroelectronics website: www.st.com.

1 STM32F10xxx I/O toggling


1.1 Overview

This example describes how to use the Port Bit Set/Reset register (GPIO BSRR) and the Port Bit Reset register (BRR) for I/O toggling.

1.2 Hardware description

Figure 1 shows the example hardware connection used. The hardware consists of 4 LEDs connected to the PC6, PC7, PC8 and PC9 pins.

Figure 1. STM32F10xxx I/O toggling



1.3 Firmware description

The provided firmware includes the GPIO driver that supports all GPIO features through a set of functions. An example of use for most of these functions is provided.

In this example GPIO, BSRR (Port Bit Set/Reset register) and BRR (Port Bit Reset register) are used for I/O toggling. With these registers, one or more GPIO pins can be modified in a single atomic write access.

This firmware is provided as GPIO example1 in the STM32F10xxx firmware library, available from the STMicroelectronics microcontroller website.

2 Using the STM32F10xxx SWJ pins as standard I/Os


2.1 Overview

This section describes how to use the GPIO firmware library to release the SWJ-DP (Serial Wire JTAG- Debug Port) pins and reuse them as standard I/Os.

2.2 Hardware description

Figure 2 shows how to connect the five LEDs to the SWJ-DP pins.

Figure 2. STM32F10xxx SWJ-DP pins used as Standard I/Os



2.3 Firmware description

The provided firmware includes the GPIO driver that supports all GPIO features through a set of functions. An example of use for most of these functions is provided.

First, the SWJ-DP is disabled. The SWJ-DP pins are configured as output push-pull. Five LEDs connected to the PA13(JTMS/SWDAT), PA14(JTCK/SWCLK), PA15(JTDI), PB03(JTDO) and PB04(JTRST) pins are toggled in an infinite loop.

Note that once the JTAG IOs are disabled, the connection with the host debugger is lost and cannot be re-established as long as the JTAG IOs remain disabled. To avoid this situation, the PB09 pin is connected to a push-button that is used to disable or not the JTAG IOs:

- push-button pressed at reset: JTAG IOs disabled
- push-button not pressed at reset: JTAG IOs unchanged

This firmware is provided as *GPIO example2* in the STM32F10xxx firmware library, available from the STMicroelectronics microcontrollers website.

2.4 Conclusion

The SWJ-DP IOs can be used as standard IOs to reach 80% of the IO ratio.

3 Revision history

Table 1. Document revision history

Date	Revision	Changes
14-Jun-2007	1	Initial release.
11-Oct-2007	2	Section 1: STM32F10xxx I/O toggling added.

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2007 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com